

AFG SLR-40 Specifications

Airflow	1653 CFM (Airflow testing conducted to panel output at STC, AM1.5, 1000 W/m2 , TC = 25°C)
HVI-916 Airflow (w/ standard louver) (for CA)	760 CFM (Airflow testing conducted to panel output at STC, AM1.5, 1000 W/m2 , TC = 25°C)
Attic SQFT Coverage @ .75 CFM per SQFT	Covers up to 2,000 SQFT
Motor Voltage	DC
Inverter Energy Use	22.1 Watts
Inverter Voltage	120 VAC, 60 Hz
# of Speeds	1
Motor Head Diameter	14.5"
Motor Head Length	7"
Solar Panel Dimensions	19.5" x 19.5"
Controls	Built-in Preset Thermostat (77 °F off and 88 °F on)
Warranty	15 Years
Shipping Weight	18 lbs.
Box Dimensions	22.5" x 22.5" x 12.5"
In The Box	- AFG SLR-40
	- 40 Watt Solar Panel
	- Accessory Bag
	- 20ft AC/DC Inverter Cable

Features & Benefits:

- 40 Watt Polycrystalline Solar Panel
- AC/DC Inverter for 24/7 cooling
- Save up to 30% on A/C related costs

• Plug and play (no wiring)

• Built-in Preset Thermostat

