



DI800-2EQ THE EQUALIZER®

ELIMINATES UNEVEN GROUND



Traction Cap™ endcaps




Integrated bubble level



Adjusts in 3/8in increments



 NOT FOR USE
NEAR ELECTRICITY

 TWIST-PROOF®



- STRONG LOCKS AND FEET
- DEEP RUNGS FOR STANDING
- SAFE WIDE BASE

250lb
LOAD CAPACITY



D1800-2EQ THE EQUALIZER®

250lb

LOAD CAPACITY

Type 1 Duty Rating

Combined Weight of User and Materials

Traction Cap™ endcaps

Interlocking side rails

Rope and pulley system

Continuous braided polyester rope

Spring loaded locks

Slip-resistant Traction-Tred® D-rungs

Everlevel® leveling system

Dual action feet

- Built-in leveling system
- Lightweight aluminum construction
- Twist-Proof® Alflo® rung joint
- Strong locks and feet
- Deep rungs for standing
- Safe wide base

SPECIFICATIONS

| Model No. | Size (ft) | Max. Safe Working Height (ft) | Max. Open Extended Length (ft) | Approx. Closed Length (ft) | Reach Height (ft) | Approx. Shipping Weight (lbs) |
|------------|-----------|-------------------------------|--------------------------------|----------------------------|-------------------|-------------------------------|
| D1816-2EQ* | 16 | 13 | 13 | 8 | 15 | 31.5 |
| D1820-2EQ | 20 | 17 | 17 | 10 | 19 | 37.5 |
| D1824-2EQ | 24 | 21 | 21 | 12 | 23 | 45.5 |
| D1828-2EQ | 28 | 25 | 25 | 14 | 27 | 56 |

*Note: D1816-2EQ is not equipped with rope and pulley

DIMENSIONS

Rails: 3 in.

Flange: 1-1/16 in.

Rung: 1-3/4 in.

Fly Width: 14-1/4 in.



Exclusive Alflo® rung joint means Twist-Proof® performance

