



## 66" TropoAir Titan

Weight = 56 lbs. in box

Weight = 48 lbs. out of box

MODEL #6HE66+LK



### REQUIREMENTS

#### MECHANICAL:

Fan must be attached to a securely anchored electrical junction box that is rated for ceiling fans. Fan must also be mounted at least 10 feet above floor level.

#### ELECTRICAL:

Requires a grounded electrical supply line of 120 volts, 60Hz, 1 amp circuit.

### FEATURES

#### MOTOR SPECS:

35W DC Motor

#### LOCATION USE:

This fan is rated cETLus and meets the standard for UL-507 and CAN/CSA-C22.2 No. 113.

#### WARRANTY:

Limited Lifetime Indoor & 10-Year Outdoor

### OPTIONS

#### AVAILABLE FINISHES:

Brushed Nickel	Part #88251-88276
Oil Rubbed Bronze	Part #88250-88275
Pure White	Part #88252-88281

#### BLADES:

Match Fan Finish

#### CONTROL:

Six speeds and reversing function is controlled by the included Hand Held remote control. An in Wall Remote Transmitter is also available.

#### LIGHTING:

An optional light fixture is **INCLUDED** with unit along with a cover if a light is not desired. Light kit consist of two medium base 60W max sockets. Included are two 13W CFL bulbs.

#### DOWNROD:

The fan comes with a nom. 3/4" diameter x 9" long down-rod. Optional down-rods are available in 12", 24", 36", 48", 60" and 72" lengths. A down-rod coupler is available for installations requiring a down-rod longer than 72". Fan can be mounted on a sloped ceiling up to 35°.

### PERFORMANCE

#### AIRFLOW/ENERGY EFFICIENCY INFO

Fan Speed	RPM	CFM/ Watt	WATT	CFM
High	95/83	303	30.8/16.6	9325
Med	70/57	589	11/7.1	6474
Low	44/30	1003	4.8/3.5	3511

Dimensions:		
Canopy Diameter	Sweep Diameter	
5 15/16"	66"	
Downrod Length	Blade Depth	All Depth
9"	16"	19"
12"	19"	22"
24"	31"	34"
36"	43"	46"
48"	55"	58"
72"	79"	82"