# COOL-SPACE 350

There for you when it matters most, Cool-Space 350 has the powerful, ecofriendly performance to carry you through the worst that summer has to offer. With its durable polyethylene housing, 8-inch thick cooling media, and a 50-gallon reservoir, this energy-efficient beast is designed to harness the full power of evaporative cooling. Install one in your outdoor patio or well-ventilated indoor space to get rapid, reliable heat relief that's simple to control.



### **KEY FEATURES**

- Quickly cool indoor and outdoor spaces by up to 33 °F (18 °C)
- Ideal for large outdoor patios
- 8-inch (20-centimeter) resin-treated cooling media
- 50-gallon (189-liter) reservoir lasts up to 10 hours without hose connection
- 20-inch (50.8-centimeter) fan diameter
- Variable speed dial and pump on/off switch or connected controller upgrade with Kick Ass™ mode and mobile app control

#### COVERAGE AREA—

UP TO

2,300 SQUARE FEET

(213.6 SQUARE METERS)

#### AIRFLOW-

UP TO 3,400 CFM

#### CONTROL-

VARIABLE SPEED WITH PUMP ON/OFF SWITCH OPTIONAL CONNECTED CONTROLLER AND APP

#### - VOLTAGE —

100-120 VAC 200-240 VAC



COMFORT WITHOUT COMPROMISE


## DISCOVER MORE ABOUT COOL-SPACE


Learn more at **bigassfans.com/evaporative-coolers** or call **877.BIG.FANS** for a free custom quote.

### COOL-SPACE® 350

#### **DELIVER COOLER CONDITIONS AT A MOMENT'S NOTICE**







Technical Specifications													
Model	Model Number	Input power and required breaker	Amperage <sup>1</sup>	Drive	Motor	Weight	Water Capacity	Inlet Water Supply Pressure	Environment <sup>2</sup>	Airflow and Coverage	Sound Level <sup>3</sup>	Operating Temperature	
Cool-Space 350	E-350-2001 E-350-2002	100–120 VAC, 60 Hz, 1Ф, 15 A 200–240 VAC, 50/60 Hz, 1Ф, 10 A	5.22 A 3.47 A	Variable Speed	1/3 hp (0.25 kW)	160 lb (69 kg)	50 gal (189 L)	60 PSI Max	Well-ventilated indoor or outdoor space	Up to 3,400 cfm Up to 2,300 sq ft	l 69 dBA	0 to 104 °F (-18 to 40 °C)	

Construction											
Housing	Motor	Power Supply	Controls	Water Supply	Cooling Media	Maintenance					
UV-resistant roto-molded polyethylene housing Four swivel casters (two locking)	High-efficiency, totally enclosed		Variable speed with pump on/off switch Optional connected controller features variable speed control, status indicators, auto-dry, Kick Ass" mode, and mobile app connectivity Connected controller enables remote control and monitoring of the cooler using the Big Ass Fans mobile app	Accepts standard garden hose or portable supply tank Water level regulated by float valve Low-water shutoff for pump longevity	Made from thick cross- corrugated, angle-fluted formulated cellulose Treated with thermosetting resin for strength and prevention of algae	Accessible reservoir cap for convenient water treatment access Drain plug and flush valve for water removal					







Onboard Variable Speed Control



Optional Connected Controller Upgrade

Lead times may vary.
See full warranty for coverage information.



Maximum amperage includes both the fan and pump ratings.
Not suitable for saft air environments.
Fans are sound tested in al absorbory environment. Actual results in field conditions may vary due to sound reflecting surfaces and environmental conditions.