

**SUPER
SEAL™**

PREMIUM



Crack Filler

For Temporary Repair of Cracks Up To 1/2" Wide in
Asphalt Driveways & Walkways. Rubberized
to Stay Pliable in Both Hot & Cold Weather.
Snip & Squeeze to Fill...
Dries in 4 - 8 Hours.

1GAL (3.78L)
www.super-seal.us

RUBBERIZED...Cold Pour Formula

**READY
TO
USE**



DALTON
ENTERPRISES, INC.

Super Seal® is a trademark of:
Dalton Enterprises, Inc.,
Cheshire, CT 06410, USA
Ph. 800-851-5606
www.super-seal.us Copyright © 2020

**SUPER
SEAL™**

PREMIUM



Crack Filler

READY-TO-USE

Remove all dirt, grass, old crack filler and debris from crack to be filled. Shake well before using. Pre-mixed, DO NOT DILUTE. Cut tip to a size slightly smaller than the width of the crack to be repaired. Squeeze/pour PREMIUM

Crack Filler slowly into the crack, DO NOT OVER FILL. Crack Filler will self-level. Wipe/clean any crack filler residue from crack surface. Do not apply more than 1/4" thick in any single application. For deep or large cracks you may fill with sand or backer rod to within 1/4" of surface before applying Crack Filler. PREMIUM Crack Filler will dry to the touch within 30 minutes and depending on outdoor conditions, should be fully dry within 4-8 hours.

CAUTION: Do not allow product to freeze. Apply when temperature is at least 55 degrees Fahrenheit and rising. Do not apply if rain is forecast within 24 hours. Do not apply in cracks wider than 1/2". Fresh PREMIUM Crack Filler will clean up with soap and water.

**KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER CAPPED WHEN NOT IN USE
NON FLAMMABLE**

⚠ WARNING: This product can expose you to Crystalline Silica, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Contents/Cas#: Asphalt #8052-42-4;
Clay #1332-58-7; Water #7732-18-5;
Refer to SDS sheet for more information.
VOC<10 g/L

