

**DEWALT®**

**PERFORMANCE  
REDEFINED™**

**XR®**



**OUR BEST PERFORMING  
20V MAX\* BATTERIES\*\***

\*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

\*\*Based on longer life (charge cycles) and more power, not in application vs. DEWALT 20V MAX\* batteries with comparable amp hours.

**GUARANTEED TOUGH.®**

**XR® BATTERIES**



# DEWALT

## XR POWERSTACK™

## XR POWERPACK™

**COMPACT SIZE**



**OVERMOLDED BASE**  
Provides additional impact resistance for drops

**FUEL GAUGE**  
LED state-of-charge indicator

**FUEL GAUGE**  
LED state-of-charge indicator



**OVERMOLDED BASE**  
Provides additional impact resistance for drops

**50%<sup>1</sup>  
MORE POWER**



1XR POWERSTACK™ DCBP520 battery vs. DEWALT DCB205 battery, not in application.  
XR POWERSTACK™ DCB2108 battery vs. DEWALT DCB2108 battery, not in application.

**LONGER  
LIFESPAN<sup>2</sup>**



2XR POWERSTACK™ DCBP520 battery vs. DEWALT DCB205 battery, based on charge cycles.  
XR POWERSTACK™ DCB2108 battery vs. DEWALT DCB208 battery, based on charge cycles.

**COMPACT  
SIZE<sup>3</sup>**



3XR POWERSTACK™ Battery Total Volume vs DEWALT XR POWERPACK™ DCB2108 battery.



### XR® BATTERY OFFERINGS

#### XR POWERSTACK™



**20V MAX\*  
XR POWERSTACK™  
COMPACT BATTERY**

**DCBP034**



**20V MAX\*  
XR POWERSTACK™  
5 AH BATTERY**

**DCBP520**

#### XR POWERPACK™



**20V MAX\*  
XR POWERPACK™  
8 AH BATTERY**

**DCB2108**

Copyright © 2024 DEWALT. The following are examples of trademarks for one or more DEWALT power tools and accessories: the yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.

DWXRBTYSS

**GUARANTEED TOUGH.®**

**1-800-4-DEWALT**

**www.DEWALT.com**