

RCD-1500EX



Carts and Dollies

SKU# 5150191

1500-Lb. Capacity Go-Cart™ Car Dollies, Jumbo, 13" Tire Width, 37" Tire Diameter, Sold as Pair

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

The Extended-Length GoCart™ is Ideal for Big Tires

The extended-length RCD1500EX car dolly offers the same 1,500-lb. weight capacity as the standard-length version, but it holds tires from 19" - 37" in diameter. This ability to secure larger tires means a set of GoCart [car dollies](#) will let you move larger, light-duty trucks and SUVs.

With multiple locks on each dolly, including both a sliding pin and a hook latch to restrict the possibility of dolly movement while you roll your vehicle, it's extraordinarily safe to move raised vehicles. The front wheels of the dolly also include an on/off lever, so the wheels cannot move once you need to lower the car and remove the dollies from the vehicle wheels.

Non-skid polymer rollers engage the wheel, safely grabbing the tires for maximum hold. The skid-proof construction guarantees custom and specialty tire/wheel configurations won't be damaged or marred.

Nearly silent urethane wheels promote safe usage on many types of flooring. Under heavy load, the urethane wheels actually improve dolly performance. Urethane is the best material for wheels, and they work on all types of terrain, including grass and dirt.

Each car dolly is finished with a durable power coat in the beautiful red gloss that has become synonymous with Ranger's recognizable brand. The coating is waterproof, fade-resistant and meant to last for years of heavy use.

Features

- Heavy-duty steel construction
- Available in sets of two or four
- Durable powder-coat finish
- Flat free polymer wheels for easy rolling
- Non-skid polymer rollers resist load slippage
- Expandable frame accommodates variable tire sizes
- Move heavy loads with confidence and ease



Specifications

Load Rating (ea.)	1,500 lbs. (680 kg)
Load Rating Total	6,000 lbs. (2,722 kg)
Lifting Mechanism	Hydraulic Foot Pump
Tire Width Capacity	13" (330 mm)
Tire Diameter Capacity	19" - 37" (483 mm - 940 mm)
Overall Height	6" (152 mm)
Casters Diameter	4" (102 mm)
Stowed Dimensions	25" x 26" (635 mm x 660 mm)
Mobile Storage Rack	Optional