

ASSEMBLING & INSTALLATION INSTRUCTIONS PRODUCT#4721 4722 4723 47184 47185 For Wall Mount Fixture

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .
ATTENTION! COUPER LE COURANT AU FUSIBLE OU LE DISJONCTEUR.**

MOUNTING THE FIXTURE

Installation (see fig.1)

1. Shut off the power at the circuit breaker and remove old fixture, including the cross bar.
2. Attach the mounting screw part way into the side hole of the crook cross bar, then lock it securely with hex nut until becoming.
3. Attach the cross bar to the junction box using two box screws as shown. **The side of the cross bar marked "GND" must face out. The junction box is not included.**
4. Follow wiring instructions carefully (see fig.2)
5. Place the fixture body (B) over the mounting plate, aligning the holes with mounting screws, then lock it securely with the ball nut(C).
6. **Install the light bulbs in accordance with the fixture's specifications. DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**
7. Raise the glass(A) insert the lamp holder and then the spring claw will hold back the end of glass.

Wiring (see fig.2)

1. Connect the electrical wires as follows. Connect the Black wire from the fixture to the black house (hot) Wire. Connect the white wire from the fixture to the white (neutral) house wire. Make sure all wire nuts are secured. You may wrap the connections with electrical tape. If your outlet box has a ground wire (green or bare copper) connect fixture's ground wire to it. Otherwise attach the bare copper fixture wire to the green ground screw on the mounting plate.
2. Tuck the wire connections neatly into the wall junction box.

Fig.1




Fig.2

FIXTURE WIRES	HOUSE WIRES	FIXTURE WIRES	HOUSE WIRES	FIXTURE WIRES	HOUSE WIRES
Black or Smooth	Black (Hot)	White or Ribbed	White (Neutral)	Bare Copper (Ground)	Green or Bare Copper (Ground)



DOC20141204721