



66" x 36" drop-in/undermount bath **K-855**

Features

- Spacious design accommodates up to two bathers
- Safeguard® slip-resistant surface provides excellent traction underfoot

Material

KOHLER® enameled cast iron

Installation

- Reversible drain
- Drop-in or undermount
- Requires cable pop-up bath drain and bath drain trim (sold separately)

Required Products/Accessories

K-23857 Bath drain trim

K-78440 33" cable pop-up bath drain

Recommended Products/Accessories

K-587 Under-Mount Installation Kit

K-23726 Drain treatment

K-23725 Cast iron cleaner

Codes/Standards

ASME A112.19.1/CSA B45.2 ASTM F462

KOHLER® Enameled Cast Iron Bath and Shower Base Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.


Color	Code	Description
	0	White
	96	Biscuit
	NY	Dune
	95	Ice™ Grey
	58	Thunder™ Grey
	7	Black Black™







KOHLER

66" x 36" drop-in/undermount bath K-855



No change in measurements if connected with drain illustrated. (K-7147-AF)





Technical Information

All product dimensions are nominal.

Drain location: Reversible

Basin area, bottom: 45" x 25" (1143 mm x 635 mm) 58" x 29" (1473 mm x 737 mm) Basin area, top:

Weight: 440 lbs (199.6 kg) Minimum floor load: 81 lbs/ft2 (395.5 kg/m2) 19-1/2" (495 mm) Water depth: Water capacity: 105 gal (397.5 L)

Cutout: Drop-in, 64-1/2" x 34-1/2" (1638 mm x

876 mm)

Template: K-587, required, not included

1-15/16" (50 mm) Minimum flat for

door:

Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will

Kit is required for under-mount installations

(sold separately).

