



WHISPER MAT® LVT

LUXURY VINYL TILE
SOUND CONTROL UNDERLAYMENT

36" x 80' ROLL

**JUST UNROLL
AND APPLY LVT**

PROPERTIES WHISPER MAT LVT

Green Approval	CRI Green Label Plus Certified for Optimal Indoor Air Quality
Applications	Residential & Commercial
Thickness	1.8 mm (70 mils)
Density	25 lb/ft ³
Content	100% Virgin Latex Rubber
Substrates	Non-Woven
Antimicrobial Protection	Yes
Roll Width	36"
Roll Length	80 ft
Roll Weight	34 lbs
Rolls/Pallet	16
Pallets/Truck	26
Full Roll	200 sf
Color	Green
Warranty	10 Year Limited Warranty

APPROVED SUBSTRATES

- Completely Cured Concrete
- Cement Backer Units
- Interior Plywood
- Properly Prepared OSB

SOUND RATINGS

Luxury vinyl tiles and planks

- 6" Concrete Floor With No Ceiling – IIC 57, STC 51
- 6" Concrete Floor With Ceiling Assembly – IIC 73, STC 63
- Delta IIC 27

LEED® POINT CATEGORIES

- 100% Post-Consumer Recyclable
- Acoustical Properties - LEED® IEQp3
- Low Emitting Materials - LEED® EQ4.3
- Regional Priority - LEED® MRc5.1, 5.2l

APPROVED FOR USE UNDER

Laminate and Luxury Vinyl Tiles & Planks

INSTALLATION METHODS

Float, Single Glue, Double Glue

SPECIFICATIONS

Material Composition: Rubber

Compression Set: ASTM D 1055-97 (22h, 70C) – 16%

Indentation: ASTM F1914 – 12%

Smoke Density: ASTM A662 – Less Than 89 Max

ASTM E84 SDI 105

Flammability Test: ASTM D 2859 (DOC FF 1-70) – Pass

ASTM E84 FSI 85

Thermal Resistance: 0.205 (R-Value)

Indoor Air Quality: CRI Certified For Low Emitting Materials



**EASY APPLICATION
FOR QUICK
INSTALLATION**