

roject:		
ixture Type:		
ocation:		
Contact:		

# **VAST**

Ceiling mounted • Dry location listed



#### **Description:**

Beautiful and expansive in design, the 72" Vast ceiling fan is ideal for use in large areas for maximum cooling. A white opal shade complements a Brushed Nickel finish with Chrome accents. Featuring an energy efficient DC motor with 18W light source, Vast is dimmable and offers a 3000K-color temperature. A full function remote control with batteries is included. Can be used to comply with California Title 20. Can be used to comply with 2016 Title 24 JA8.

### **Specifications:**

- Brushed Nickel (-09) (plated)
- · Steel construction
- · Frosted Glass bowl
- Eight-blade 72" Vast ceiling fan features an LED light source, offering both form and function with energy- and cost-savings benefits.
- · Vast ceiling fan features Brushed Nickel blades with a Brushed Nickel finish and Chrome accents.
- The light kit contains a frosted glass shade and is comprised of a 18W dimmable 3000K LED module, offering 1400 lumens, 90+ CRI.
- As a general rule of thumb, lighting experts suggest this fan is ideal in a room size that is larger than 400-square feet.
- A 3/4" x 6" downrod is included. Longer accessory downrods can be ordered separately.
- Mounting hardware is included.
- · Dimmable to 10% brightness (See Dimming Notes)
- · Canopy covers a standard 4" octagonal recessed outlet box
- · 80" of wire supplied
- Brushed Nickel blades, aluminum construction
- 14 degree blade pitch
- · Six Speed Full Function Remote Control Included
- · Six speed, manual reverse control
- · Meets California Title 24 JA8-2016
- · Airflow: 7982 CFM\*
- · Energy consumtion: 28 watts (excluding lights)\*
- · Airflow efficiency: 285 cfm/watt\*
- · \* Fan on a downrod

## P2550-0930K

#### **Images:**




#### **Dimensions:**

Diameter: 72" Height: 16-3/4"

#### Performance:

Number of Modules	1	
Input Power	18w	
Input Voltage	120 V	
Input Frequency	60 Hz	
Lumens/LPW	1400/77.8 (LM-79)	
ССТ	3000 K	
CRI	90+	
Life (hours)	(L70/TM-21)	
EMI/RFI	FCC Title 47, Part 15 Class B	
Min. Start Temp	-30 ℃	
Max. Operating Temp	30 ℃	
Warranty	Limited Lifetime warranty	
Labels	UL Dry location listed	
	Meets California Title 24 JA8-2016	





# **VAST**

Ceiling mounted • Dry location listed PROGRESS LED

## P2550-0930K

### **Dimming Notes:**

P2550 is designed to be compatible with many controls.

The following is a partial list of known compatible dimmer controls.

### **Dimming Controls**

Lutron - NTEVL-300

Lutron - DVELV-300P

Lutron-DVCL-253P

Lutron - Caseta Wireless

IDevices - IDEV009

Leviton - 6672

Leviton – 6674

Lutron - AYCL-153P

Lutron - TGCL-153-PH-WH

Lutron - AYLV-600P

Lutron - MAELV-601

Leviton -AWSMT-EAW

Lutron - N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.