



INSTALLATION

1. Remove the existing shower head from the shower arm pipe. Clean the shower arm threads with a soft brush.
2. Hand-tighten the swivel end-coupler onto the threaded shower arm.
3. If leakage occurs, wrap the shower arm pipe threads with Teflon tape.

OPERATION

BEFORE ENTERING THE SHOWER

1. Activate and flush the filter by running hot water through the filtered shower head for 1 minute before using.
2. COOL TO DESIRED TEMPERATURE BEFORE ENTERING SHOWER.

MAINTENANCE

1. Replace the filter cartridge (model SLC) every 4-6 months or 10,000 gallons, whichever comes first.

FILTER CARTRIDGE REPLACEMENT (MODEL SLC)

1. To Open: Unscrew 2-piece shower head housing.
2. Remove used filter cartridge and O-rings.
3. Clean and lubricate O-rings with petroleum jelly.
4. Reinstall the O-rings.
5. To Close: Screw 2-piece shower head housings together.

RECYCLE FILTER CARTRIDGE

1. Carefully poke a hole in the screen of the filter cartridge and empty contents into garden soil.
2. Place the filter cartridge in with recyclables.



1791 Railroad St., Corona, CA 92880 U.S.

Phone: 800-327-9137 (US Toll Free)
or 951-735-1015

1791 Railroad St, Corona, CA 92880 EE. UU.

Teléfono: 800-327-9137 (gratis en EE. UU.)
o 951-735-1015

1791 Railroad St, Corona, CA 92880 États-Unis

Téléphone: 800-327-9137 (appel gratuit)
ou 951-735-1015



USE & CARE INSTRUCTIONS

Filtered Shower Head

Instrucciones de uso y cuidado CABEZAL FILTRADO MODELO AG

Instructions d'utilisation et d'entretien POMMEAU DE DOUCHE AVEC FILTRE MODEL AG

PERFORMANCE DATA: MODEL SLC FILTER CARTRIDGE

Maximum Rated Service Flow –
2.5 gallons per minute /
9.5 liters per minute

**Maximum Rated Service Life
for Free Chlorine removal** –
4-6 months or 10,000 gallons /
37,854 liters (whichever comes first)

Maximum Working Pressure –
125 pounds per square inch /
860 kilo pascals.

Maximum Operating Temperature –
120° Fahrenheit / 49° Celsius.

NOTE:

- While testing was performed under laboratory conditions. Actual performance may vary.
- This system is not intended to be used as a drinking water treatment unit.
- Both the system and installation must comply with applicable state and local regulations.

This Sprite Shower Filtration System has been tested for reduction of free chlorine. The concentration of free available chlorine in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system. This system has not been evaluated for free chlorine reduction in the presence of chloramines. Free chlorine reduction performance may be impacted by the presence of chloramines in the water supply.

LIMITED ONE YEAR WARRANTY

Sprite Industries, Inc. warrants the Filtered Shower Head housing only (not the cartridge) to be free of defects for a period of one (1) year when used under normal operating conditions. At the time of purchase, it is the owner's responsibility to complete the warranty information available on-line at www.spriteshowers.com, keep proof of purchase of the unit and all replacement cartridge(s) and demonstrate that proper filter maintenance was performed. The provisions of this warranty shall not apply to any product that has been subject to misuse, neglect, over-tightening, lack of, or improper filter replacement, repaired or altered by anyone other than a Sprite service representative and will VOID the warranty in its entirety. Transportation charges on units submitted for repair or replacement under warranty to Sprite Industries, Inc. 1791 Railroad St, Corona, CA 92880 shall be paid by the registered owner. This is the exclusive remedy and liability for consequential damages. There are no other warranties, either expressed or implied, limited to the extent permitted by law.

FOR MORE INFORMATION AND ON-LINE REGISTRATION

Go to: www.spriteshowers.com