

ASSEMBLY INSTRUCTIONS



CAUTION

◆ Inspect the wire insulation for any cuts, abrasions, or exposed copper that may have resulted during shipping. If there is a defect in the wire, do not attempt installation.

◆ Before starting installation of this fixture or removal of a previous fixture, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.



If you need further assistance, please contact us by Email: customersupport@superiordecorinc.com

TOOLS REQUIRED



Ladder



Safety glasses



Electrical tape




Phillips screwdriver



Flat blade screwdriver



Pliers




Wire strippers

HARDWARE INCLUDED




Fixture




Glass Shade



Iron Ring



Mounting Unit



Ball Nuts




Mounting Screws



Wire Nuts

***PARTS SHOWN MAY DIFFER SLIGHTLY PER LIGHT FIXTURE**




EXPLODED PARTS



INSTALLATION


STEP 1

Adjust arms to proper position.



STEP 2


Unscrew the **ball nuts** from the **mounting unit**. Use the **mounting screws** to attach the **mounting unit** to the junction box (not included).



ASSEMBLY INSTRUCTIONS (INSTALLATION)


STEP 3

Make the electrical connection from the junction box (not included) to the **fixture**. Connect the ground wire to the **mounting unit** using the preinstalled green ground screw. Next, connect the positive, negative and ground wires with the supplied **wire nuts**. Secure with electrical tape.




STEP 4

Secure the **fixture** to the **mounting unit** with the **ball nuts**.



STEP 5

Install bulb (not included)



STEP 6

Place the **iron ring** and **glass shade** onto the **fixture**, the secure with **ball nuts**.

