

VersaPro® 80% AFUE GAS FURNACE

MGA80SE*****C



- ✓ 80% AFUE
- ✓ Quiet Operation
- ✓ Superior Performance
- ✓ Durable Build & Finish
- ✓ Optional LP Kit
- ✓ All-Position
- ✓ Single Stage
- ✓ Energy Efficient
- ✓ Compact Design

Upflow, downflow, horizontal flow. R-454B
refrigerant leakage sensor adaptable.



SCAN HERE
for the most up-to-
date version of this
brochure.



48 Remington Way
Hickory, KY 42051
270.366.0457

www.mrcool.com

Version Date: 05-30-2025



VersaPro® 80% AFUE GAS FURNACE[‡]

MGA80SE*

In the face of even the harshest winter conditions, the MRCOOL® VersaPro® 80% AFUE Gas Furnace guarantees reliable and high quality warmth and comfort within your home. Its sturdy construction and space-efficient design cater to various cabinet sizes, facilitating easy installation, replacement, and maintenance, even in areas where space is limited.

The furnace's single stage ECM motor ensures energy efficiency and cost savings, while the hot-surface ignition ensures dependable operation you can count on.

The blower operates quietly, seamlessly integrating with your daily activities without disruption. Its AHRI certification and ETL listing guarantee the unit has undergone rigorous testing to meet the highest quality and performance standards.

Designed for multi-position installation: Up flow, down flow, and horizontal. Industry-standard cabinet sizes for easy replacement, installation and add-on cooling. Convenient left or right connection for gas and electric service, and a removable bottom for side or bottom return applications.

Registering the furnace within 90 days of installation activates a 10-year parts warranty and lifetime heat exchanger warranty, providing peace of mind.* Even without registration, your unit is protected by a 5-year parts warranty and 20-year heat exchanger warranty, promising long-term reliability and comfort.

SPECIFICATION

GAS FURNACE - 80% AFUE

MODEL NO		Unit	MGA80SE040A3C	MGA80SE060B4C	MGA80SE080B4C	MGA80SE080C4C	MGA80SE100C5C	MGA80SE120D5C
Power Supply		V-Hz, Ph	115-60, 1	115-60, 1	115-60, 1	115-60, 1	115-60, 1	115-60, 1
Nat. Gas/LP	Input	Btu/h	40,000	60,000	80,000	80,000	100,000	120,000
	Output	Btu/h	32,000	48,000	64,000	64,000	80,000	96,000
Blower Size		inch	11.18 x 6.14	11.18 x 9.64	11.18 x 9.64	11.18 x 11.18	11.18 x 11.18	12.75 x 11.25
Temperature Rise Range		°F	20-50	25-55	30-60	30-60	30-60	35-65
Cabinet Size (WxDxH)		inch	14.5 x 28.75 x 33.75	17.5 x 28.75 x 33.75	17.5 x 28.75 x 33.75	21 x 28.75 x 33.75	21 x 28.75 x 33.75	24.5 x 28.75 x 33.75
Packing Size (WxDxH)		inch	17 x 31.02 x 40.74	20 x 31.02 x 40.74	20 x 31.02 x 40.74	23.5 x 31.02 x 40.74	23.5 x 31.02 x 40.74	27 x 31.02 x 40.74
Motor		HP	1/2	1/2	1/2	1/2	1	1
Max Airflow Rate (0.5ESP)		CFM	1150	1300	1300	1300	1750	1950
Motor Speeds			5 speed	5 speed	5 speed	5 speed	5 speed	5 speed
Gas Type			NG (LP w/kit)	NG (LP w/kit)	NG (LP w/kit)	NG (LP w/kit)	NG (LP w/kit)	NG (LP w/kit)
Gas Connection Size		inch	3/4	3/4	3/4	3/4	3/4	3/4
Gross Weight		lbs	132	141	155	163	177	190



Data provided by AHRI



[‡]Registered Warranty provides for a total of 10 years of limited warranty coverage (Standard 5-year limited parts warranty plus an additional 5-year limited extended parts warranty; Lifetime heat exchanger warranty when registered). Warranty must be registered online within 60 days of installation to qualify for extended coverage. Unregistered equipment defaults to 5-year coverage.