

WHITE

WHITE

WHITE

WHITE

WHITE

DAP®

DAP®

DAP®

BASEBOARDS

WINDOWS

DOORS

MOLDING

TRIM

CAUTION! Contains ethylene glycol. May cause mild skin irritation. Do not get in eyes, on skin or clothing. Use gloves and safety glasses. Use in well-ventilated area. Do not ingest. **In an emergency,** call your poison control center at 800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN.**

¡PRECAUCIÓN! Contiene etilenglicol. Puede causar irritación leve de la piel. Evite el contacto c/los ojos, la piel y la ropa. Use guantes y gafas de seguridad. Use en un área bien ventilada. No lo ingiera. **En caso de emergencia,** llame a un centro de control de envenenamiento al 800-222-1222. Para más información, consulte la Hoja de datos de seguridad (SDS). Para obtener una SDS, comuníquese con su proveedor o visite dap.com. **MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠ WARNING Cancer & Reproductive Harm / ADVERTENCIA Cáncer y daños al sistema reproductor—

www.P65warnings.ca.gov

NCCS Calif. ARB VOC
< 1.5% wt/wt (VOC 27 g/L)



QUESTIONS?/PREGUNTAS?

Call/Llame al **888-DAP-TIPS** or visit/o visite dap.com & click/on y pulse en "Ask the Expert."

DAP Products Inc.
Baltimore, MD 21224

Made in the
USA with U.S.
and globally
sourced
materials.
dap.com

ALEX® STRETCH

Exceeds ASTM C920, Class 25

ACRYLIC URETHANE ELASTOMERIC SEALANT



- 2 HOUR PAINT READY
- FILLS GAPS UP TO 3"
- MULTI-SURFACE ADHESION
- CRACKPROOF & WATERPROOF
- EASY WATER CLEAN UP & LOW ODOR
- INTERIOR/EXTERIOR

Paint Projects

DAP® ALEX® STRETCH ACRYLIC URETHANE ELASTOMERIC SEALANT is a high performance sealant ideal for sealing a wide variety of interior & exterior surfaces such as windows, doors, siding, trim, molding, sinks, countertops & more. It stretches over 600% and provides superior adhesion & long-lasting durability. ALEX STRETCH forms a flexible, 100% waterproof & weatherproof seal to withstand environmental conditions. It is easy to apply & tool, paintable, low in odor & cleans up with water. Cured sealant is mold & mildew resistant. VOC compliant.

FOR BEST RESULTS: Apply in temperatures above 40°F. Do not apply when rain or freezing temperatures are forecasted within 24 hours. Cooler temps & higher humidity will slow down dry time. Not for continuous underwater use, filling butt joints, surface defects or tuck-pointing. Joint size should not exceed 3" wide x 1/2" deep. If joint depth exceeds 1/2", use backer rod material. Store away from extreme heat or cold.

INSTRUCTIONS: 1. Surface must be clean, dry & free of old caulk & foreign material. 2. Cut nozzle at a 45° angle to desired bead size. 3. Load cartridge into caulk gun. 4. Fill gap with sealant. 5. Smooth/tool bead. 6. Clean excess wet sealant with damp sponge before it skins over. Dried sealant must be cut or scraped away. 7. Paintable after 2 hours (longer in cool/humid conditions) with latex or oil-based paints. 8. Reseal cartridge for storage & reuse.

COVERAGE: 55 linear ft at 3/16" diameter bead.

LIFETIME GUARANTEE: DAP warrants this product for sealant purposes during the lifetime of your home, when used as directed, within one year of purchase. Call **888-DAP-TIPS**, with your sales receipt and product container available for replacement product or sales price refund. DAP is not liable for incidental or consequential damages.

Para obtener las instrucciones y garantía en español, llame al **888-DAP-TIPS** o visite dap.com.

Read back panel for cautions!
¡Lea las precauciones en el
panel posterior!

10.1 fl oz (300 mL)