

ITEM	TENIA Model	Description	
			6681
80350	T-L3C12D-4.5W	C12 candle, frost torpedo, 120V,60Hz , 4.5W,300lm, 2700K (2725±145K) , E26 base, PC cover, dimmable,Luminus LED chip, ETL& Energy Star approved	YES
80776	T-L4C16A2TD-7W	C16 candle, clear tip PC cover, E12 base,120V,60Hz , 7W,500lm, 2700K (2725±145K),,260°Beam angle, Dimmable,Bridgelux LED chip, ETL& Energy Star approved Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80772	T-L3C12A2TD-4.5W	C12 candle, clear tip PC cover ,4.5W,300lm,E12 base, 2700K (2725±145K) ,,260°Beam angle, Dimmable,Bridgelux LED chip, ETL&Energy Star approved, Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
40983	T-L 12MR16D-7W-CCOB-LI	MR16 spot light, SMD copy COB, E26 base, PC lens, 7W,120V,60Hz,500lm, 2700K(2725±145K),35° beam angle, Dimmable, ETL approved, not ES product. Package:Color box/6pcs,Master box/72pcs	YES
80143	T-L 12MR16D-7W-CCOB-LI	MR16 spot light,SMD copy COB,E26 base,PC lens, 120V,60Hz, 7W,500lm,5000K(5028±283K),35° Beam angle, Dimmable, ETL approved, Not ES product. Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80521	T-L 12MR16D-7W-CCOB-LI	MR16 spot light, SMD copy COB, GU10 base, PC lens,Matt finish. 7W,120V,60Hz, 500lm,2700K (2725±145K) ,35° beam angle, Dimmable, ETL&Energy Star approved.Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80522	T-L 12MR16D-7W-CCOB-LI	MR16 spot light, SMD copy COB, GU10 base, PC lens,Matt finish. 7W,120V,60Hz, 500lm,3000K(3045±175K),35° beam angle, Dimmable, ETL&Energy Star approved.Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80527	T-L 12MR16D-7W-CCOB-LI	MR16 spot light, SMD copy COB, GU10 base, PC lens,Matt finish. 7W,120V,60Hz, 500lm,4000K(3985±275K),35° beam angle, Dimmable, ETL&Energy Star approved.Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80528	T-L 12MR16D-7W-CCOB-LI	MR16 spot light, SMD copy COB, GU10 base, PC lens,Matt finish. 7W,120V,60Hz, 500lm,5000K(5028±283K),35° beam angle, Dimmable, ETL&Energy Star approved.Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80529	T-L 12MR16D-7W-CCOB-LI	MR16 spot light, SMD copy COB, GU10 base, PC lens,Matt finish. 7W,120V,60Hz, 500lm,6500K(6530±510K),35° beam angle, Dimmable, ETL&Energy Star approved.Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80769	T-L3C12A2D-4.5W-LI	C12 candle, Clear PC cover ,Non-tip,4.5W,300lm,Ra80 E12 base,3000K(3045±175K),260° Beam angle, Dimmable,ETL&Energy Star approved.Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES

80775	T-L3C12A2D-4.5W-LI	C12 candle, Clear PC cover ,Non-tip,4.5W,300lm,Ra80 E12 base, 4000K(3985±275K),260° Beam angle, Dimmable,ETL&Energy Star approved.Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80777	T-L3C12A2D-4.5W-LI	C12 candle, Clear PC cover ,Non-tip,4.5W,300lm,Ra80 E12 base,5000K(5028±283K),260° Beam angle, Dimmable,ETL&Energy Star approved.Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80778	T-L3C12D-4.5W-LI	C12 candle, Frost PC cover ,Non-tip,4.5W,300lm,Ra80 E12 base,3000K(3045±175K),180° Beam angle, Dimmable,ETL&Energy Star approved.Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80779	T-L3C12D-4.5W-LI	C12 candle, Frost PC cover ,Non-tip,4.5W,300lm,Ra80 E12 base, 4000K(3985±275K),180° Beam angle, Dimmable,ETL&Energy Star approved.Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80781	T-L3C12D-4.5W-LI	C12 candle, Frost PC cover ,Non-tip,4.5W,300lm,Ra80 E12 base,5000K(5028±283K),180° Beam angle, Dimmable,ETL approved,ETL approved,ES product, Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80782	T-L4C16A2D-7W-LI	C16 candle, Clear PC cover ,Non-tip,7W,500lm,Ra80 E12 base,3000K(3045±175K),260° Beam angle, Dimmable,ETL&Energy Star approved.Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80783	T-L4C16A2D-7W-LI	C16 candle, Clear PC cover ,Non-tip,7W,500lm,Ra80 E12 base, 4000K(3985±275K),260° Beam angle, Dimmable,ETL&Energy Star approved.Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80785	T-L4C16A2D-7W-LI	C16 candle, Clear PC cover ,Non-tip,7W,500lm,Ra80 E12 base,5000K(5028±283K),260° Beam angle, Dimmable,ETL&Energy Star approved.Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
40980	T-L9PAR30SD-9W-CCOB-LI	PAR30,Short neck,Copy COB,PC lens,E26 base, 120V,60Hz,10W,850lm,3000K(3045±175K), 35° Beam angle, Dimmable, ETL&Energy Star approved,Linear IC, Package:Color box/6pcs,Master box/36pcs	YES
40306	T-L7G16.5D-7W-LI	G16.5,Frost PC cover,E12 base,120V,60Hz,7W, 500lm,2700K(2725±145K),180° beam angle, Dimmable,ETL& Energy Star approved, Package:Color box/6pcs,Master Box/72pcs	YES
40293	T-L6G16.5A2D-5W-LI	G16.5,Clear PC cover,E12 base,120V,60Hz,5W, 500lm,2700K(2725±145K),180° beam angle, Dimmable,ETL& Energy Star approved, Package:Color box/3pcs,Master Box/72pcs	YES
80425	T-L2R14D-4W-LI	R14,Frost PC cover,120V,60Hz,E17 base,4W, 250lm, 3000K(3045±175K),105° beam angle, Dimmable,ETL approved,Not ES product, Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80437	T-L12MR16D-6W-CCOB-LI	MR16 spot light, SMD copy COB, E26 base, PC lens,Matt finish. 6W,120V,60Hz, 500lm,2700K (2725±145K) ,35° beam angle, Raa90,PF>0.9, Dimmable, ETL+TL24,.Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES

80438	T-L12MR16D-6W-CCOB-LI	MR16 spot light, SMD copy COB, E26 base, PC lens,Matt finish. 6W,120V,60Hz, 500lm,3000K(3045±175K),35° beam angle, Raa90,Dimmable, ETL+TL24,Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80439	T-L12MR16D-6W-CCOB-LI	MR16 spot light, SMD copy COB, E26 base, PC lens,Matt finish. 6W,120V,60Hz, 500lm,4000K(3985±275K),35° beam angle,Raa90,Dimmable, ETL+TL24,Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80440	T-L12MR16D-6W-CCOB-LI	MR16 spot light, SMD copy COB,E26 base, PC lens,Matt finish. 6W,120V,60Hz, 500lm,5000K(5028±283K),35° beam angle, Raa90,Dimmable, ETL+TL20,Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80551	T-L12PAR16D-6W-CCOB-LI	PAR16,Spot light ,Copy COB,120V,60Hz,E26 base, 6W,500lm,5000K(5028±283K),35° Beam angle,Ra90 Dimmable,Satify ETL&ES&Title20(Tier 2),Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80553	T-L12PAR16D-6W-CCOB-LI	PAR16,Spot light ,Copy COB,120V,60Hz,E26 base, 6W,500lm, 2700K(2725±145K),35° Beam angle,Ra90 Dimmable,Satify ETL&ES&Title20(Tier 2),Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80966	T-L9PAR30SD-9W-CCOB-LI	PAR30,Short neck,Copy COB,PC lens,E26 base,120V,60Hz, 9W,750lm ,2700K(2725±145K), 35° Beam angle, Ra90 ,PF>0.7 Dimmable, Satify ETL&ES& Title20(Tier 2) , Linear IC , Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80967	T-L9PAR30SD-9W-CCOB-LI	PAR30,Short neck,Copy COB,PC lens,E26 base,120V,60Hz, 9W,750lm ,3000K(3045±175K), 35° Beam angle, Ra90 ,PF>0.7 Dimmable, Satify ETL&ES& Title20(Tier 2) , Linear IC , Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80968	T-L9PAR30SD-9W-CCOB-LI	PAR30,Short neck,Copy COB,PC lens,E26 base,120V,60Hz, 9W,750lm ,4000K(3985±275K), 35° Beam angle, Ra90 ,PF>0.7 Dimmable, Satify ETL&ES& Title20(Tier 2) , Linear IC , Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80969	T-L9PAR30SD-9W-CCOB-LI	PAR30,Short neck,Copy COB,PC lens,E26 base,120V,60Hz, 9W,750lm ,5000K(5028±283K), 35° Beam angle, Ra90 ,PF>0.7 Dimmable, Satify ETL&ES& Title20(Tier 2) , Linear IC , Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80982	T-L4C16A2D-7W-LI	C16 candle, Clear PC cover, Non-tip,E12 base,120V,60Hz,7W, 500lm, 2700K(2725±145K),,260°Beam angle, Ra90 ,PF>0.7 Dimmable,Satify ETL&ES& Title20(Tier 2) , Linear IC , Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80983	T-L4C16A2TD-7W-LI	C16 candle, clear tip PC cover, E12 base,120V,60Hz,7W,500lm, 2700K(2725±145K),,260°Beam angle, Ra90 ,PF>0.7 Dimmable,Satify ETL&ES& Title20(Tier 2) , Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80984	T-L3C12A2D-4.5W-LI	C12 candle, Clear PC cover ,Non-tip,4.5W,300lm,E26 base, 2700K(2725±145K),260°Beam angle, Ra90 ,PF>0.7 Dimmable,Satify ETL&ES& Title20(Tier 2) , Linear Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80754	T-L3C12A2D-4.5W-LI	C12 candle, Clear PC cover ,Non-tip,4.5W,300lm,E12 base, 2700K(2725±145K),260°Beam angle, Ra90 ,PF>0.7 Dimmable,Satify ETL&ES& Title20(Tier 2) , Linear Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES

80755	T-L3C12A2TD-4.5W-LI	C12 candle, Clear PC cover, with tip,4.5W,300lm,E12 base, 2700K(2725±145K),260°Beam angle,Ra90,PF>0.7 Dimmable,Satify ETL&ES&Title20(Tier 2),Linear Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
41614	T-L4C16A2D-7W-LI	C16 candle, Clear PC cover, Non-tip,E26 base,120V,60Hz,7W, 500lm, 2700K(2725±145K),,260°Beam angle,Ra90,PF>0.7 Dimmable,Satify ETL&ES&Title20(Tier 2),Linear IC, Package:Color box/6pcs,s,Master box/72pcs	YES
40289	T-L7G16.5A2D-7W-LI	G16.5, Clear PC cover,E26 base,120V,60Hz,7W, 500lm, 2700K(2725±145K),Ra80,PF0.7,Linear IC 260° beam angle, Dimmable,ETL&Energy Star approved. Package:color box/3pcs,Inner box/18pcs,Master box/72pcs	YES
80943	T-L9PAR30LD-9W-LI	PAR30,Long neck,Copy COB,PC lens,E26 base, 120V,60Hz,9W,850lm,4000K(3985±275K), 35° Beam angle, Dimmable, ETL&Energy Star approved,Linear IC, Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80653	T-L6G16.5D-5W-LI	G16.5,Frost,PC cover,E26 base,120V,60Hz,5W,350lm, 2700K(2725±145K),Ra80,PF0.7,180° beam angle, Dimmable,ETL&Energy Star approved.Linear IC ,Linear IC, Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80774	T-L4C16A2D-7W-LI	C16 candle, Clear PC cover ,Non-tip,7W,500lm,Ra80 E12 base,2700K(2725±145K),260°Beam angle, Dimmable,ETL&Energy Star approved.Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80518	T-L6G16.5A2D-5W-LI	G16.5, Clear PC cover,E26 base,120V,60Hz,7W, 350lm, 2700K(2725±145K),Ra80,PF0.7,Linear IC 260° beam angle, Dimmable,ETL&Energy Star approved. Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES
80529	T-L12MR16D-7W-CCOB-LI	MR16 spot light, SMD copy COB, GU10 base, PC lens,Matt finish. 7W,120V,60Hz, 550lm,6500K(6530±510K),35° beam angle, Dimmable, ETL&Energy Star approved.Linear IC Package:Color box/1pcs,Inner box/6pcs,Master box/24pcs	YES

[illegible]

[illegible]

[illegible]

[illegible]

Dimmer List Version

LUTRON

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]