

DEWALT

MULTI-FUEL. MULTI-PURPOSE POWER.

10500W TRI-FUEL OPEN FRAME GENERATOR

The DEWALT 10500W Tri-Fuel open frame portable generator is designed with the professional in mind. The generator is powered by a premium 500cc DEWALT electric start engine with low oil shut off which protects the engine from damage. The Idle control feature conserves fuel and reduces noise on the job site while CO-Protect Technology automatically shuts down the generator if CO levels become unsafe or rapidly increase. The generator provides feedback to the user with its Smart runtime meter showing how much runtime is left based on fuel consumption. Equipped with GFCI protected outlets for job site compliance and safety. The wattage meter gives instant feedback on how much power is being used. Never flat durable wheels provide maximum portability and durability. The 7.9 Gal. steel fuel tank provides 9 hours of runtime at 50% load while running on gasoline. Liquid propane and natural gas fuel types are also supported on this Tri-Fuel generator.

GASOLINE

13000 STARTING WATTS

10500 RUNNING WATTS

PROPANE

11250 STARTING WATTS

8550 RUNNING WATTS

NATURAL GAS

9000 STARTING WATTS

7000 RUNNING WATTS



TRI FUEL

10500W TRI-FUEL OPEN FRAME GENERATOR



FEATURES

- **CO-Protect Technology:** Carbon Monoxide Shutdown.
- **Premium DEWALT OHV Engine:** 500cc with splash lubrication provides a long engine life.
- **Smart Runtime Meter:** Shows fuel level (gas) and time remaining at current power level.
- **Wattage Meter:** Gives instant feedback on how much power is being used.
- **Idle Control:** Conserves fuel and reduces noise on the job site.
- **Low-oil Level Shutdown:** Automatically safeguards engine from damage.
- **Electric Start (Battery Included):** Provides hassle-free start-up.
- **Hardened 1 1/4" Steel Tube Cradle:** For added durability and strength.
- **Covered Outlets:** Provide protection from the elements and rugged working conditions.
- Handle and Heavy-Duty Wheel Kit included.

SPECIFICATION

MODEL NUMBER	PMC2610500
UPC	696471107708
ENGINE SIZE	500cc OHV
RATED AC VOLTAGE	120/240V
RUNNING WATTS GASOLINE	10500W
RUNNING WATTS LPG	8550W
RUNNING WATTS NG	7000W
STARTING WATTS GASOLINE	13000W
STARTING WATTS LPG	11250W
STARTING WATTS NG	9000W
RATED AMPS	87.5/43.75A
RATED FREQUENCY (@3600 RPM)	60 Hz
RUN TIME @ 50% LOAD (GAS)	9 Hours
RUN TIME @ 50% LOAD (20LB OF LPG)	4 Hours
RUN TIME @ 50% LOAD (NG)	Continuous*
ASSEMBLED UNIT DIMENSIONS	27.4" x 28.2" x 27.0" (695 mm x 716mm x 686 mm)
FUEL TANK SIZE	7.9 Gal. (30 L)
DRY WEIGHT	225.8 lb (102.4 kg)
PACKAGED WEIGHT	246.7 lb (111.9 kg)

WARRANTY

**GENERATOR
WARRANTY**



**LIMITED
WARRANTY**

OUTLET TYPES



(2) 20 AMP
120V 5-20R GFCI



(1) 30 AMP
120/240V L14-30R



(1) 50 AMP
120/240V 14-50R

*Dependent on grid supply and maintenance intervals

© 2026 DEWALT®, GUARANTEED TOUGH® and the yellow/black color scheme are trademarks for DEWALT power tools, outdoor equipment, accessories, anchors, and concrete adhesives and are used under license. Product may differ from that pictured. Does not affect function.

Manufactured under license by
Generac Power Systems, Inc.
S45 W29290 Hwy. 59, Waukesha, WI 53189
generac.com | 888-431-6871
201912180 | 07/2026