# **MOEN**<sup>®</sup>

# Specifications

#### DESCRIPTION

- Construction with various finishes identified by suffix
- · Includes handshower, wallmount, hose & diverter
- 1/2" IPS connection

#### **OPERATION**

- Handheld: 6 function featuring pause
- Wallmount: 8 function featuring pause
- Rotate outer ring to select on showerheads
- · 3-way diverter provides ability to flow each showerhead separately or combined for more coverage
- Diverter includes pause button to pause water flow easily

#### FLOW

• Designed to deliver 1.75 gpm (6.6 L/min) MAX at 80 psi

#### **STANDARDS**

- Third party certified at WaterSense<sup>®</sup>, ASME A112.18.1/CSA B-125.1, and all applicable specifications referenced therein
- Products marked with 1.75 gpm are compliant with California water efficiency regulations

#### WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- · 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation Visit www.moen.com/support for complete details and limitations



## Attune™

8-Function Handshower & Wallmount with Diverter & Hose

#### MODELS: 218C0 Series





### **CRITICAL DIMENSIONS** DO NOT SCALE



3-08-2022

