



98702S-986: 4 Inch 2700K High Output LED Module-986 Dimensions:



Length: 4"
Width: 7/8"
Height: 5/8"

Bulb Type: Array
Volts: 12
Watts: 4
Watts Consumed: 4
Watts Rated: 4
Hours Rated: 50000
Lumens: 220
Bulb Temp: 2700 °K
CRI: 90

Features:

- This advanced LED technology is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability.

Material List:

1 Body - Aluminum - Tinted Aluminum

Safety Listing:

Safety Listed for Damp Locations

Collections: Lx High Output LED Modules (Primary)
Lx Components

The miniature, high output LED modules can be used with 12 volt Lx Cable Systems powered by magnetic low-voltage or zero-load electronic low-voltage transformers, High Output LED Modules are dimmable on magnetic and electronic low voltage systems. For magnetic systems, a magnetic low voltage (MLV) dimmer should be used. For electronic, an electronic low voltage (ELV) dimmer is recommended.

Delivers higher light levels with wider spacing - up to 12" on center-use fewer modules per installation

Energy efficient uses only 4 watts, up to 85% energy savings vs. incandescent

Contains 9 integrated top tier multi-LED chip packages

Long life light source, lasts up to 50,000 hours

Color accurate illumination +85 CRI

2700K color temperature (warmer white), also available in 3000K color temperature (warm white)

Thermally efficient, low profile anodized aluminum housing with gray molded end caps runs cooler to maximize life of LEDs

Performance independently tested to IES LM79 standards

UPC #:785652218637

Shade / Glass / Diffuser Details:

Part	Material	Finish	Quantity	Item Number	Length	Width	Height	Diameter	Fitter Diameter	Shade Top Length	Shade Top Width	Shade Top Diameter
------	----------	--------	----------	-------------	--------	-------	--------	----------	-----------------	------------------	-----------------	--------------------

Sea Gull Lighting reserves the right to revise the design of components of any product due to parts availability or change in safety listing standards without assuming any obligation or liability to modify any products previously manufactured and without notice. This literature depicts a product design that is the sole and exclusive property of Sea Gull Lighting . In compliance with U.S copyright and patent requirements, notification is hereby presented in this form that this literature, or the product it depicts, is not to be copied, altered or used in any manner without the express written consent of, or contrary to the best interests of Sea Gull Lighting 1/2 A Generation Brands Company.

Diffuser	Acrylic	Frosted	1								
----------	---------	---------	---	--	--	--	--	--	--	--	--

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Fr. Class	UPS Ship
Individual	98702S-986	1	785652218637	4.38	1.2	1.2	0.004	0.1	60	Yes
Master Pack	98702S-986	200	10785652218634	5.25	9.25	11	0.309	19.4	60	Yes
Shipping Master	98702S-986	200	20785652218631							
NJ Pallet		10800		48	40	72	80	1047.6		No