

Strong-Bond™ Fast-Cure Anchoring and Bonding Adhesive



Blue is wet.

Gray is set.™



SIMPSON
Strong-Tie

Strong-Bond™
with **Color Cure™**

Blue is Wet Gray is Set

Fast-Cure Anchoring and Bonding Adhesive
Adhesivo de anclaje y unión de curado rápido
Adhésif d'ancrage et de liaison à durcissement rapide

Fast Curing
Curado rápido
Durcissement rapide

Light/Medium Use
Uso ligero/medio
Utilisation légère/moyenne

All Seasons
Todas las estaciones
Toutes les saisons

10.1 fl. oz. 300 mL

WARNING: May cause skin and/or eye irritation. See back panel for additional information. KEEP OUT OF REACH OF CHILDREN.
PRECAUCIÓN: Puede causar irritación de la piel y/o de los ojos. Ver panel posterior por advertencias adicionales.
DANGER: Éloigner des enfants. Éviter le contact avec les yeux.
DANGER: Peut causer l'irritation des yeux ou de la peau. Voir les avertissements supplémentaires au verso.
DANGER: ÉLOIGNER DES ENFANTS.

(800) 999-5099
strongtie.com

Strong-Bond™ Fast-Cure Anchoring and Bonding Adhesive

SIMPSON

Strong-Tie

Introducing Strong-Bond fast-curing anchoring and bonding adhesive from Simpson Strong-Tie — the ideal solution for everyday anchoring and repair of concrete, masonry and stone applications. The unique Color Cure™ technology allows Strong-Bond to dispense blue and turn gray when cured, making installation simple and fast. The cartridge fits into a standard caulking tool and is easy to prepare, keeping your projects on track. Designed to cure quickly — even in below-freezing temperatures — Strong-Bond is ready when you are. Whether you're anchoring threaded rod into concrete, doweling rebar, or bonding stone, Strong-Bond delivers professional results every time.

Features

- Blue-to-gray color change indicating cure
- Coaxial cartridge design
- Fast-set formulation
- Cures below 32°F
- Suitable for wet or dry conditions

Cure Schedule

°F	°C	Working time	Cure time
14	-10	50 min.	4 hrs.
32	0	20 min.	1.5 hrs.
50	10	9 min.	1 hr.
68	20	5 min.	30 min.
86	30	3 min.	20 min.
104	40	3 min.	20 min.

Do not apply loads until after cure time.

Cartridge must be conditioned to at least 68°F prior to use.

Cartridge System Table

Model No.	Capacity (oz.)	Cartridge Type	Carton Qty.	Dispensing Tool	Mixing Nozzle
STRGBND10	10.1	Coaxial	6	CDT10S	Included



Key Applications

- Secure handrails
- Mount gates/fencing to brick or concrete
- Secure rebar
- Hang lights, signs, TVs
- Fix large cracks/repair damaged concrete
- Mount hooks for bikes, ladders, garden tools
- Bond decorative blocks/stone

This flyer is effective until December 31, 2027, and reflects information available as of October 1, 2025. This information is updated periodically and should not be relied upon after December 31, 2027. Contact Simpson Strong-Tie for current information and limited warranty or see strongtie.com.

© 2025 Simpson Strong-Tie Company Inc. • P.O. Box 10789, Pleasanton, CA 94588

S-A-STRONGBND25 10/25 exp. 12/27

(800) 999-5099
strongtie.com