# 9723/9725/9728 INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later

### **CAUTION**

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock

#### **GENERAL**

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

#### ASSEMBLY AND INSTALLATION

- 1. Lock the loop and tube (16) on the nipple (17) of the fixture.
- 2. Attach mounting bar (6) with threaded nipple (10) and screw collar loop (12) and lock ring (13) to outlet box (1) secured with two box screws (9).
- 3. Attach quick links (15) to the screw collar loop (12) and the appropriate amount of chain (15).
- 5. Slide the lock ring (13) and the canopy (11) down the chain (14). Open the quick link (15) at the other end and then hook onto top of fixture (16), close the quick links.
- 6. Thread the wires through the chain and the screw collar loop (12) and thread nipple (10) up to outlet box.
- 7. Pull out the outlet wire and ground wire from the outlet box Make wire connections with wire nuts.
- --Ribbed wire (W/O marking) or white wire from light to White wire (2) from power source.
- --Smooth wire (W marking) or black wire from light to Black wire (3) from power source.
- --Attach the ground wire (4) to mounting bar (7) with a ground screw (8).
- 8. Raise canopy (11) against ceiling and lock it in position by lock ring (13) onto The screw collar loop (12).
- 9. Place the glass shade (20) onto the socket (19), then secure with socket ring (21).
- 10. Aligning the hole of bottom ring (22) to the arm tube of fixture body (18), securing with set screws (23)
- 11. Install bulbs: (bulbs not included)
  (Don't exceed the maximum capacity recommended on the sockets).

1.OUTLET BOX 2.WHITE WIRE 3.BLACK WIRE **4.GROUND WIRE** 5.WIRE NUT 6.MOUNTING BAR 7.GROUND SCREW 8.HEX NUT 12 9.BOX SCREW 13 10.NIPPLE -15 11.CANOPY -14 12.SCREW COLLAR LOOP 13.LOCK RING 14.CHAIN -15 15.QUICK LINK -16 **16.LOOP AND TUBE** 17.NIPPLE **18.FIXTURE BODY** -17 19.SOCKET 20.GLASS -18 21.SOCKET RING 22.BOTTOM 23.SET SCREW -21 -20 19

## **INSTALLATION IS NOW COMPLETED**