


SPECIFICATIONS

Height	23.875 in.
Width	23.875 in.
Area	4 sq. ft. (nominal)
Features	Recess 0.50 in. from tile face
Collection	Feather-Light
Thickness	0.013 in.
Weight	6.4 oz. (0.10 lb. per sq. ft.)
Material	Laminated rigid vinyl
Color	Copper
Finish	Brushed Metallic
Cut-out	6 in. cut-out available
Perforation	Available



INSTALLATION

Installation Type	Standard drop (15/16 to 1 in.)
Borders	Yes, this style may be trimmed for use along borders
Direct Mount Grid	Yes, this product may be used with direct mount grid
Temp. Warning	Not recommended for installation where ceiling temperatures exceed 120°F

CERTIFICATIONS, LISTINGS, APPROVALS

Drop-out Installation	Yes, approved for installation <u>beneath</u> fire suppression sprinklers
	IAPMO Uniform ES Listing Report 5021
	IAPMO Uniform ES Evaluation Report 0310
	FM Class 4651
	FM Certificate of Compliance

Fire Ratings	NFPA 13
	CertMark Evaluation Report CMI-ER31001
	Class A
	Euroclass Rating B-s2-d0
Code Compliance	Flame Class V-0
	2015, 2012, 2009, and 2006 IBC
Indoor Air Quality	Greenguard Gold Certified; low-VOC; dust and fiber free
Food Preparation	FDA and USDA Compliant
Moisture	FEMA Class 4 Material; waterproof; washable
Sustainability	100% recyclable

PERFORMANCE

Noise Reduction	NRC 0.25
	NRC 0.25 with perforations
	NRC 0.30 with AcoustoTherm
	NRC 0.40 with perforations and AcoustoTherm
	NRC 0.50 with Soniguard
	NRC 0.85 with perforations and Soniguard
Sound Transmission	STC 10
	STC 11 with AcoustoTherm
	STC 13 with Soniguard
Ceiling Attenuation	CAC 14
	CAC 20 with Soniguard
Light Reflectance	57.46%
Thermal Insulation	R-0.012
	R-0.80 with AcoustoTherm
	R-6.0 with Soniguard