



EQUATOR®
ADVANCED Appliances ≡



All-in-One Combo Washer-Dryer

VENTING

Sanitize • Allergen • Winterize • PET Cycle

Equator All-in-One Washer Dryer VENTED-DRY 30% FASTER than Condense 15lb 110V + Pedestal

HIGHLIGHTS



- QR Code
- Touch Buttons
- ADA Compliant
- 2 Min Winterize Cycle
- Color Coded LED Display
- Anti Bacterial Drum Baffle
- Dual fans for Faster Drying
- Low Water Pressure Valves
- Diagnostics (13 error codes)
- Automatic Water & Dry Level
- Pedestal with Storage Drawer
- Allergen Cycle Kills Dust Mites
- Sanitize Cycle Disinfects Clothes
- Pet Cycle: Special program to remove pet hair.
- Compliant with Prop 65 (California)

AVAILABLE IN



Black

Silver

FEATURES

- Child lock
- Delay Start
- Oversuds Control
- Add-a-sock option
- End of cycle chime
- Start / Pause function
- Easy to open coin trap
- Adjustable Leveling legs - 4
- Easy to install - remove 2 shipping rods
- Electronic control panel with LED Lights
- Energy saving - auto display off after 5 min
- Angled 45° Door handle (Reduces bending)
- Venting Booster fan option to blow air 50 ft (Extra Accessory)



White

WASH CYCLES

- NORMAL
- Prewash
- Heavy
- ECO
- Quick 20
- Delicate
- Wool
- Quiet 60 db
- Allergen
- Sanitize
- PET Cycle

DRY CYCLES

- Sensor Dry
- Time Dry 60 min
- Refresh 12 min

OPTIONS

- Drain
- Self-Clean
- Winterize

SPECIFICATIONS

Model	EZ 4800 V + PDL 4455
Colors	White, Black and Silver
Capacity	1.62 cu.ft. / 15 lbs.
Programs	15
Door Diameter / Swing	18" / 180°
Dry Ventilation	Venting
Wash Only & Dry Only Option	Yes
Pre-Wash Function	Yes
Automatic Door Lock in Wash	Yes
Water Intake in Drum	Circumference & Back
Stainless Steel Drum	Yes, Pearl Design
Spin Speed	1400 rpm
Exhaust Fan	0.5 A
Fan Motor	65 Watt
Electrical	110V / 60Hz / 12A
Weight (Net/Gross) lbs	161 / 163
Product Dimensions HxWxD (inch)	33.5 x 23.6 x 21.8
Pedestal Dimension HxWxD (inch)	11.25 x 23.5 x 22.25
Product Dimension HxWxD (inch) With Pedestal	44.75 x 23.6 x 22.25
Packaging Dimensions HxWxD (inch)	35 x 26 x 22.5
Type of Shipping	LTL
Certification	ETL
Warranty	1 Year Parts and Labor

Keywords: Sanitize, Allergen cycle, Anti-Bacterial drum baffles, Winterize, Color coded LED Display, Quiet Cycle, Delay Start



Equator Advanced Appliances • 10222 Georgibelle Drive, Suite 200 • Houston, TX 77043-5249

Toll Free: 800-935-1955 • Fax: 832-202-2732 • www.EquatorAppliances.com • E-Mail: mail@equatorappliances.com

Super Combo - Model EZ 4800 V

DEFINITIONS

Venting Combo: The dryer air is exhausted externally from the machine

ENERGY SAVING

Automatic Water Level: Weighs the clothes to automatically use the correct amount of water required

Sensor Dry: Moisture sensor selects the correct amount of time to dry the clothes

Delay Start: Set the start time up to 24 hours later, in one hour increments

INNOVATIVE WASHING

Winterize Cycle: Winterize your machine in 2 minutes. Pour antifreeze and Start

Allergen Cycle: Special cycle to kill dust mites. The water is heated to 131° F and kept at that temp for 3 minutes

Sanitize Cycle: Water is heated to 165° F to sanitize clothes. Perfect for people working in contaminated environments to protect family eg. hospital

Quiet Cycle: Clothes are washed and dried at low RPM with noise level less 60 dB. Perfect for families working in different shifts, babies and seniors

BETTER DRYING

Exhaust fan: Super Combo has an exhaust fan that will work in the venting cycle, in addition to the turbo blower fan. This dries the clothes faster

Refresh function: A 12 minute hot dryer cycle to refresh clothes before folding

SPECIAL FEATURES

Self-clean option: Runs a short wash to clean the drum

Child lock: Locks all operations during a cycle so a child cannot operate it

Pause: Stop the operations at any time of the cycle for any reason

Add-a-Sock: Open the door during a wash cycle to add clothes

End of cycle chime: The machine will chime at the end of the program every 5 minutes until any button is pressed or the door is opened

PET Cycle: Special program to remove pet hair.

FASTER SERVICE

Built-in Diagnostics: Choice of 13 error codes inform the user of possible problems, reducing down-time for service

