

# **Material Safety Data Sheet**

Copyright, 2012, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

# **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME:**G82, Perfect Clarity Glass Cleaner (24-125A): G8224**MANUFACTURER:**Meguiar's, Inc.**DIVISION:**Meguiar's

ADDRESS: 17991 Mitchell South, Irvine, CA 92614

**Telephone:** 949-752-8000 (Fax: 949-752-5784)

### EMERGENCY PHONE: CHEMTREC 1-800-424-9300 (24 hours)

<b>Issue Date:</b>	11/19/12
Supercedes Date:	01/23/12

Document Group: 29-9787-2

### **Product Use:**

Intended Use: Specific Use: Automotive Glass cleaner

# **SECTION 2: INGREDIENTS**

IngredientC.A.S. No.% by WtNON-HAZARDOUS INGREDIENTSMixture77 - 972-BUTOXYETHANOL111-76-21 - 5ISOPROPYL ALCOHOL67-63-01 - 5

# **SECTION 3: HAZARDS IDENTIFICATION**

### 3.1 EMERGENCY OVERVIEW

Odor, Color, Grade: Sweet odor; off-white

#### MATERIAL SAFETY DATA SHEET G82, Perfect Clarity Glass Cleaner (24-125A): G8224 11/19/12

#### **General Physical Form:** Liquid **Immediate health, physical, and environmental hazards:**

May cause target organ effects.

## **3.2 POTENTIAL HEALTH EFFECTS**

#### **Eye Contact:**

Mild Eye Irritation: Signs/symptoms may include redness, pain, and tearing.

#### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

#### **Target Organ Effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Blood Effects: Signs/symptoms may include generalized weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and/or hemoglobinemia.

## **SECTION 4: FIRST AID MEASURES**

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

#### MATERIAL SAFETY DATA SHEET G82, Perfect Clarity Glass Cleaner (24-125A): G8224 11/19/12

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

# **SECTION 5: FIRE FIGHTING MEASURES**

## 5.1 FLAMMABLE PROPERTIES

Autoignition temperature Flash Point Flammable Limits(LEL) Flammable Limits(UEL) No Data Available Flash point > 93 °C (200 °F) No Data Available No Data Available

## 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

## 5.3 **PROTECTION OF FIRE FIGHTERS**

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Not applicable.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

### **6.2.** Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

### **Clean-up methods**

Observe precautions from other sections. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with water.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

# **SECTION 7: HANDLING AND STORAGE**

## 7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid breathing of vapors, mists or spray. Avoid eye contact with vapors, mists, or spray. Keep out of the reach of children. Avoid contact with oxidizing agents.

## 7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Store away from areas where product may come into contact with food or pharmaceuticals. Store away from oxidizing agents.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Use in an enclosed process area is recommended. Use in a well-ventilated area. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

### 8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray. The following eye protection(s) are recommended: Safety Glasses with side shields

### 8.2.2 Skin Protection

Not applicable. Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials. Gloves made from the following material(s) are recommended: Butyl Rubber Nitrile Rubber

### 8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray. Do not breathe vapors.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

### 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

## 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	Type	<u>Limit</u>	Additional Information
1,2-Propanediol	AIHA	TWA, as aerosol	10 mg/m3	
2-BUTOXYETHANOL	ACGIH	TWA	20 ppm	
2-BUTOXYETHANOL	OSHA	TWA	240 mg/m3	Skin Notation*
ISOPROPYL ALCOHOL	ACGIH	TWA	200 ppm	
ISOPROPYL ALCOHOL	ACGIH	STEL	400 ppm	
ISOPROPYL ALCOHOL	OSHA	TWA	980 mg/m3	

\* Substance(s) refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

#### SOURCE OF EXPOSURE LIMIT DATA: ACGIH: American Conference of Governmental Industrial Hygienists CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Odor, Color, Grade: General Physical Form: Autoignition temperature Flash Point Flammable Limits(LEL) Flammable Limits(UEL) Boiling Point Density Vapor Density

**Vapor Pressure** 

Specific Gravity pH Melting point

Solubility in Water Evaporation rate Volatile Organic Compounds Kow - Oct/Water partition coef VOC Less H2O & Exempt Solvents Viscosity Sweet odor; off-white Liquid *No Data Available* Flash point > 93 °C (200 °F) *No Data Available No Data Available* 0.99 g/ml *No Data Available No Data Available* 

0.99 [*Ref Std:* WATER=1] 4.5 - 5.5 *No Data Available* 

Complete No Data Available 3.00 % No Data Available No Data Available No Data Available

# **SECTION 10: STABILITY AND REACTIVITY**

### Stability: Stable.

Materials and Conditions to Avoid: 10.1 Conditions to avoid Heat

**10.2 Materials to avoid** Strong acids Strong oxidizing agents

Hazardous Polymerization: Hazardous polymerization will not occur.

### **Hazardous Decomposition or By-Products**

<u>Substance</u> Carbon monoxide Carbon dioxide <u>Condition</u> During Combustion During Combustion

# **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

# **SECTION 12: ECOLOGICAL INFORMATION**

### ECOTOXICOLOGICAL INFORMATION

Not determined.

## **CHEMICAL FATE INFORMATION**

Not determined.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Discharge spent solutions and small quantities of less than 5 gallons (20 liters) to a municipal or industrial wastewater treatment system.

As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

#### Since regulations vary, consult applicable regulations or authorities before disposal.

## **SECTION 14: TRANSPORT INFORMATION**

General Transportation Statement This product does not require classification by DOT, IATA, ICAO or IMDG.

# ID Number(s):

14-1000-7053-2

# **SECTION 15: REGULATORY INFORMATION**

### **US FEDERAL REGULATIONS**

Contact manufacturer for more information

#### **311/312 Hazard Categories:**

Fire Hazard - No Pressure Hazard - No

Reactivity Hazard - No

Immediate Hazard - Yes

Delayed Hazard - Yes

#### Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient	C.A.S. No	% by Wt
2-BUTOXYETHANOL (GLYCOL ETHERS)	111-76-2	1 - 5

### STATE REGULATIONS

Contact manufacturer for more information

### **CHEMICAL INVENTORIES**

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact manufacturer for more information

## INTERNATIONAL REGULATIONS

Contact manufacturer for more information

#### This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: OTHER INFORMATION**

#### NFPA Hazard Classification

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes: Not available

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. Meguiar's, Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's, Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's, Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's, Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's, Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's, Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from Meguiar's, Inc.

#### Meguiar's, Inc. USA MSDSs are available at www.Meguiars.com