

5-INCH 9.5 HP 277 CC KINETIC DRUM CHIPPER

ITEM NUMBER

OPC525

9

UPC

827518008560

DESCRIPTION

The OPC525 5-inch kinetic chipper is powered by a KOHLER® Command PRO® CH395 9.5 HP 277 cc engine and features dual swing chutes, double edge reversible high-speed cutting blades, bearing-mounted ATV tires and rims and built in toolbox with an extended load chute with safety e-stop.

The engine delivers 13.9 ft/lb torque for superior cutting performance, and the dual V-belt direct drive and kinetic cyclonic drum pulverize up to 5-inch diameter trees. The tool-free dual swing chutes quickly open for easy drum access. The feed chute features dual integrated handles for easy equipment moving, and finally this machine comes equipped with a quick-drop stand, and a 1-7/8 inch ball removable tow bar to move around job sites with ease.

SPECIFICATION

ENGINE KOHLER® Command PRO® CH395 9.5 HP 277 cc

GEARBOX 13.9 ft/lb (18.8 Nm) gross torque

WHEELS & TIRES 175/70-6 Ø13.5" (Ø34.3 cm) OD x 5" (12.7 cm) tires on Ø6" (15.2 cm) x 4.5" (11.4 cm) bearing-mounted ATV rims

CHIPPING CAPACITY Ø5" (Ø12.7 cm)

CUTTERS Double edge reversible chipper blades

CHIPPER Auto-adjusting up to Ø5" (Ø12.7 cm) trees and brush

EXPULSION CHUTE Tool-free swing open and 180° adjustable

COUPLER 1-7/8" (4.76 cm)

DIMENSIONS 91" (L) x 30" (W) x 46" (H)
231.1 cm (L) x 76.2 cm (W) x 116.8 cm (H)

WEIGHT 308.6 lb (140 kg)

SHIPPING DIMENSIONS 35.8" (L) x 22" (W) x 37.8" (H)
91 cm (L) x 56 cm (W) x 96 cm (H)

SHIPPING WEIGHT 352.7 lb (160 kg)

WARRANTY 3-year KOHLER® engine
1-year DK2 chassis



FEATURES

- Powered by a KOHLER® Command PRO® CH395 9.5 HP 277 cc engine **1**
- Chips through trees and branches up to 5" (12.7 cm) in diameter
- Dual-belt drive drum transmission with double edge reversible cutting blades for trees and brush up to 5" (12.7 cm) in diameter **2**
- 175/70-6 Ø13.5" (Ø34.3 cm) OD x 5" (12.7 cm) tires on Ø6" (Ø15.2 cm) x 4.5" (11.4 cm) bearing-mounted ATV rims for off-road performance **3**
- Extra-large extended feed chute with integrated equipment moving handles and E-stop safety shutoff **4**
- Dual tool-free swing open chutes for easy drum access
- 180° tool-free rotational spout on expulsion chute
- Removable tow bar with 1-7/8" (4.76 cm) hitch receiver
- Includes 3-year KOHLER® engine and 1-year DK2 chassis warranty
- OFF-ROAD ONLY AND MAX SPEED 15MPH (24KM/H)**

