7089D45MAB ASSEMBLY INSTRUCTIONS

Disclaimer:

Thank you for your purchase. Please read carefully and keep these instructions, as you may need them later.

We suggest installation by a licensed electrician.

Beware of potential electrical shock ! Before installing the fixture or removing any other light already present, please turn off the main power at the circuit breaker. If your product contains glass items, please handle with care, as glass is fragile and can lead to injuries if handled incorrectly.

Please keep in mind that the warnings and instructions present in this document are not meant to cover and prevent all possibilities and situations that could lead to injury or damage. It is the responsibility of the end-user to exercise caution and common sense when handling and installing the product.

All electrical connections must be made by qualified personnel in accordance with the National Electrical Code.

Please refer to the table below for electrical connections:

Fixture wire markings:	AC power equivalent:
"L" Live wire (Black or Brown)	"L" Live wire (Black)
"N" Neutral wire (White or Blue)	"N" Neutral wire (White)
"≟" Ground wire (Green or Bare)	"≟" Ground wire (Green or Bare)

For installation, please refer to the written instructions at the back.

<u>Need to contact us?</u> Please send an email at: service@aloadecor.com

Need more information? Please visit our website: www.aloadecor.com



Installation instructions:

1.Select the type of installation you require before assembly and installation: This luminaire can be installed as a Pendant or Close to Ceiling. Refer to the corresponding instructions and diagram for the different installation methods.

Pendant lamp

Step 1.Install the pole(J) onto the screw (K) and tighten the screws(L) with a small wrench(M) (included) .

Step 2. The chain is adjustable .And pass the cord and earth wire through the chain(H), canopy(F) and mounting bracket(D).

Step 3. Use the two screws(E) secure long mounting bracket(D) to the junction box.

Step 4.Install the chain onto ring(G) by activity buckle(H) .

Step 5.Twist the brass ground wire"E/ with the M4 green threaded screw on the mounting bracket and lock it to the GND position. Then twist the two ground wires together (one is the brass ground wire"E/, the other is the ground wire from the junction box, and tighten it by the terminal nut.

Step 6.Black wire from junction box attaches to "L" wire for the fixture by terminal nut ;white wire attaches to "N" wire by terminal nut.

Step 7.Use the screw nut(G) secure canopy(F) to the mounting bracket(D).

Step 8.Install the bulbs(not included).

Step 9. Hang the bottom frame(R) on the lamp body(N) by the hook chains(Q) .

Step 10. Hang the glass pieces(A/B/C) onto the lamp frame in the order shown in the diagram. Alternatively, you can hang them in any order you prefer.

