Klean-Strip Brush Cleaner / Paint Clean Up

VOC Compliant

Page: 1 of 7

Revision: 04/17/2015 Supersedes Revision: 03/17/2015

1. PRODUCT AND COMPANY IDENTIFICATION

Klean-Strip Brush Cleaner / Paint Clean Up VOC Compliant **Product Name:**

W. M. Barr **Company Name: Phone Number:**

2105 Channel Avenue (901)775-0100

Memphis. TN 38113

Web site address: www.wmbarr.com

Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346

Information: W.M. Barr Customer Service (800)398-3892

Intended Use: Spray gun cleaning.

Product Code: GBC12C, QBC12C, QBC12CW

Additional Information This product is regulated by the United States Consumer Product Safety Commission

> and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to

using the product.

2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 2

Serious Eye Damage/Eye Irritation, Category 2

Specific Target Organ Toxicity (single exposure), Category 3

Aspiration Toxicity, Category 2







GHS Signal Word:

Danger

GHS Hazard Phrases: Highly flammable liquid and vapor.

May be harmful if swallowed and enters airways.

Causes serious eve irritation.

May cause drowsiness or dizziness.

GHS Precautionary Phrases: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing gas/mist/vapors/spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Keep cool.

GHS Response Phrases:

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin

with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Page: 2 of 7

Revision: 04/17/2015

Supersedes Revision: 03/17/2015

SAFETY DATA SHEET

Klean-Strip Brush Cleaner / Paint Clean Up

VOC Compliant

Do NOT induce vomiting.

If eye irritation persists, get medical advice/attention. In case of fire, use dry chemical powder to extinguish.

GHS Storage and Disposal

Phrases:

Store container tightly closed in well-ventilated place.

Store locked up.

Dispose of contents/container according to local, state and federal regulations.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects

Inhalation Exposure Effects:

(Acute and Chronic): Vapor harmful. High concentrations may lead to central nervous system effects

(drowsiness, dizziness, nausea, headaches, paralysis, and loss of consciousness and even death). High vapor concentrations are irritating to the eyes, nose, throat, and lungs. Intentional misuse of this product by deliberately concentrating and inhaling can be

harmful or fatal.

Skin Contact Exposure Effects:

Moderately irritating to the skin. Prolonged or repeated contact can result in defatting and

drying of the skin which may result in skin irritation and dermatitis (rash).

Eye Contact Exposure Effects:

Contact with the eye may cause moderate to severe irritation.

Ingestion Acute Exposure Effects:

Product may be harmful or fatal if swallowed. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage. May produce central nervous system effects, which may include dizziness, loss of balance and coordination, unconsciousness,

coma and even death.

Target Organs: Central Nervous System, Respiratory System, Eye, Skin

Primary Routes of Entry: Inhalation, Ingestion

Medical Conditions Generally Diseases of the skin, eyes, and lung (asthma-like conditions).

Aggravated By Exposure:

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS#	AS # Hazardous Components (Chemical Name)	
67-64-1	Acetone {2-Propanone}	60.0 -100.0 %
123-86-4	Butyl acetate {n-Butyl acetate. Acetic acid, Butyl ester}	< 5.0 %

Additional Chemical

Specific percentage of composition is being withheld as a trade secret.

Information

Page: 3 of 7

Revision: 04/17/2015

Supersedes Revision: 03/17/2015

VOC Compliant

Klean-Strip Brush Cleaner / Paint Clean Up

4. FIRST AID MEASURES

Emergency and First Aid

Procedures:

Inhalation:

If user experiences breathing difficulty, move to air free of vapors, Administer oxygen or

artificial medical assistance can be rendered.

Skin Contact:

Wash with soap and large quantities of water and seek medical attention if irritation from

contact persists.

Eye Contact:

Flush with large quantities of water for at least 15 minutes and seek immediate medical

attention.

Ingestion:

Do not induce vomiting. Call your local poison control center, hospital emergency room

or physician immediately for instructions to induce vomiting.

Signs and Symptoms Of

Exposure:

See Potential Health Effects.

5. FIRE FIGHTING MEASURES

NFPA Class IB

0.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash) Flash Pt:

UEL: 13 % LEL: 1.7 % Explosive Limits:

Autoignition Pt: No data.

Suitable Extinguishing Media: Use carbon dioxide, dry powder, water spray, or alcohol resistant foam.

Unsuitable Extinguishing

Media:

None known.

Self-contained respiratory protection should be provided for fire fighters fighting fires in Fire Fighting Instructions:

> buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have

been exposed to intense heat or flame.

Flammable Properties and

Hazards:

Extremely flammable. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by an ignition source, such as pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at location distant from the material handling point. Product residue can ignite

explosively. Do not weld or cut on empty containers.

Hazardous Combustion

Carbon monoxide and carbon dioxide, other various unburned hydrocarbons.

Products:

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or

Vapors may cause flash fire or ignite explosively.

Spilled: Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying

areas, confined spaces, etc.

Small spills: Take up with sand, earth or other noncombustible absorbent material and

Licensed to W.M. Barr and Company

GHS format

Revision: 04/17/2015

Supersedes Revision: 03/17/2015

SAFETY DATA SHEET

Klean-Strip Brush Cleaner / Paint Clean Up

VOC Compliant

place in a plastic container where applicable.

Large spills: Dike far ahead of spill for later disposal.

Waste Disposal: Dispose in accordance with applicable local, state and federal

regulations.

Keep out of drains, sewers, and bodies of water.

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

Precautions To Be Taken in Storing:

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
Acetone {2-Propanone}	ACGIH TLV	TLV: 500 ppm STEL: 750 ppm	
	OSHA PELs	PEL: 1000 ppm	
Butyl acetate {n-Butyl acetic acid, Butyl ester}	ACGIH TLV	TLV: 150 ppm STEL: 200 ppm	
	OSHA PELs	PEL: 150 ppm	
	Acetone {2-Propanone} Butyl acetate {n-Butyl	Acetone {2-Propanone} OSHA PELs Butyl acetate {n-Butyl ACGIH TLV cetic acid, Butyl ester}	Acetone {2-Propanone} ACGIH TLV TLV: 500 ppm STEL: 750 ppm OSHA PELs PEL: 1000 ppm Butyl acetate {n-Butyl ACGIH TLV TLV: 150 ppm STEL: 200 ppm

Respiratory Equipment (Specify Type):

For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV.

For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

Eye Protection: Safety glasses, goggles or face shields are recommended to safeguard against potential

eye contact, irritation, or injury.

Protective Gloves: Wear gloves with as much resistance to the chemical ingredients as possible. Glove

> materials such as natural rubber and neoprene may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded

and not reused.

Various application methods can dictate use of additional protective safety equipment, Other Protective Clothing:

such as impermeable aprons, etc., to minimize exposure.

Engineering Controls (Ventilation etc.):

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - Stop - ventilation is inadequate. Leave area immediately.

Klean-Strip Brush Cleaner / Paint Clean Up

VOC Compliant

Revision: 04/17/2015 Supersedes Revision: 03/17/2015

Work/Hygienic/Maintenance

Wash hands thoroughly after use and before eating, drinking, or smoking.

Do not eat, drink, or smoke in the work area. Practices:

Discard any clothing or other protective equipment that cannot be decontaminated.

Facilities storing or handling this material should be equipped with an emergency

eyewash and safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: [X] Liquid [] Solid [] Gas

Appearance and Odor: Water White / Free and Clear

:Ha No data. Melting Point: No data. **Boiling Point:** 131.00 F

Flash Pt: 0.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)

> 1 Evaporation Rate:

Flammability (solid, gas): No data available.

LEL: 1.7 % **Explosive Limits:** UEL: 13 %

No data.

Vapor Pressure (vs. Air or

mm Hg):

Vapor Density (vs. Air = 1): > 1 Specific Gravity (Water = 1): 0.792

6.592 LB/GL Density: Solubility in Water: Complete Octanol/Water Partition No data.

Coefficient:

Percent Volatile: 100.0 % by weight. VOC / Volume: 24.0000 G/L Autoignition Pt: No data. **Decomposition Temperature:** No data.

Viscosity: No data.

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]

Conditions To Avoid -No data available.

Instability:

Incompatibility - Materials To Strong oxidizing agents.

Avoid:

2-Propanone may form explosive mixtures with chromic anhydride, chromyl alcohol, hexachloromelamine, hydrogen peroxide, permonosulfuric acid, potassium tertbutoxide,

and thioglycol.

Hazardous Decomposition or Decomposition may produce carbon monoxide, carbon dioxide, and unidentified organic

compounds in black smoke. Byproducts:

Possibility of Hazardous Will occur [] Will not occur [X]

Reactions:

No data available. Conditions To Avoid -

Hazardous Reactions:

Page: 6 of 7

Revision: 04/17/2015

Supersedes Revision: 03/17/2015

Klean-Strip Brush Cleaner / Paint Clean Up

VOC Compliant

11. TOXICOLOGICAL INFORMATION

Toxicological Information: This product has not been tested as a whole. Refer to section 2 for acute and chronic

effects.

CAS# 67-64-1:

Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe.

Result:

Behavioral: Change in motor activity (specific assay). Behavioral: Alteration of classical conditioning.

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite

1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# **Hazardous Components (Chemical Name)** NTP IARC **ACGIH OSHA** Acetone {2-Propanone} 67-64-1 n.a. n.a. A4 n.a. 123-86-4 Butyl acetate {n-Butyl acetate. Acetic acid, Butyl ester} n.a. n.a. n.a. n.a.

12. ECOLOGICAL INFORMATION

General Ecological

Information:

No information available for this product as a whole.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with all applicable local, state, and federal regulations.

Keep out of sewers and bodies of water.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Paint Related Material

DOT Hazard Class: 3 FLAMMABLE LIQUID

UN/NA Number: UN1263 Packing Group: II



Additional Transport

Information:

123-86-4

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

Yes 5000 LB

No

15. REGULATORY INFORMATION

No

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

Butyl acetate {n-Butyl acetate. Acetic acid, Butyl

CAS # Hazardous Components (Chemical Name) S. 302 (EHS) S. 304 RQ S. 313 (TRI)
67-64-1 Acetone {2-Propanone} No Yes 5000 LB No

ester}

CAS # Hazardous Components (Chemical Name) Other US EPA or State Lists

67-64-1 Acetone {2-Propanone} TSCA: Inventory
123-86-4 Butyl acetate {n-Butyl acetate. Acetic acid, Butyl CWA NPDES

ester} TSCA: Inventory

Klean-Strip Brush Cleaner / Paint Clean Up **VOC Compliant**

Revision: 04/17/2015 Supersedes Revision: 03/17/2015

Page: 7 of 7

Regulatory Information:

16. OTHER INFORMATION

04/17/2015 Revision Date:

W.M. Barr EHS Dept (901)775-0100 Preparer Name:

Additional Information About No data available.

This Product:

Company Policy or

Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.