

### SECTION 1 : IDENTIFICATION

Product Name: KILZ® Adhesion Primer

Product Code: L2111 SDS Manufacturer Number: L2111

Masterchem Industries LLC Manufacturer Name: 3135 Old Highway M Address Imperial, MO 63052-2834

General Phone Number: (636) 942-2510 Customer Service Phone (800) 325-3552

Emergency Phone Number:

Access Code:

For emergencies in the US & Canada, call Verisk 3E: 866-519-4752

February 05, 2014 SDS Creation Date: February 29, 2016 SDS Revision Date:

# SECTION 2 : HAZARD(S) IDENTIFICATION

GHS Pictograms:

Signal Word: Warning.

Eye Irritant, Category 2B. Skin Irritant, Category 2. GHS Class:

Hazard Statements: Causes eye irritation. Causes skin irritation.

Precautionary Statements: Wear protective clothing, gloves, eye, and face protection.

Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

Dispose of unused contents, container, and other contaminated wastes in accordance with local, state,

federal, and provincial regulations.

If in eyes: Rinse cautiously with water for several minutes and remove contacts if present and easy to

do. Continue rinsing and get medical attention if eye irritation persists.

If on skin: Wash with plenty of soap and water.

If swallowed: Rinse mouth and get medical attention if you feel unwell.

Emergency Overview: Irritant.

Route of Exposure: Eves, Skin, Inhalation, Ingestion,

Potential Health Effects:

Eye: Causes eye irritation. Causes skin irritation.

Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.

Ingestion: May be harmful if swallowed. May cause vomiting.

Chronic Health Effects: Prolonged or repeated contact may cause skin irritation. Signs/Symptoms: Overexposure may cause headaches and dizziness.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing

Conditions:

None generally recognized.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
Dipropylene glycol monomethyl ether	34590-94-8	1 - 5 by weight	
Nepheline Syenite	37244-96-5	10 - 30 by weight	
Titanium dioxide	13463-67-7	10 - 30 by weight	

#### SECTION 4: FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of

the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue

1 - 5 by weight

rinsing. Get medical attention, if irritation or symptoms of overexposure persists.

Skin Contact: Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained

personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give

anything by mouth to an unconscious person

1

1

0

#### SECTION 5: FIRE FIGHTING MEASURES

Flash Point: None.

Lower Flammable/Explosive Limit: Not applicable. Upper Flammable/Explosive Limit: Not applicable.

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires

involving this material.

As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear. Protective Equipment:

**NFPA Ratings:** 

NFPA Health: NFPA Flammability: NFPA Reactivity:

### SECTION 6 : ACCIDENTAL RELEASE MEASURES

Personal Precautions: Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use

proper personal protective equipment as listed in Section 8.

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Methods for containment: Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by

covering, diking or other means. Provide ventilation.

Clean up spills immediately observing precautions in the protective equipment section. Place into a Methods for cleanup:

suitable container for disposal. Provide ventilation. After removal, flush spill area with soap and water

to remove trace residue.

### SECTION 7: HANDLING and STORAGE

Handling: Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.

Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and Storage:

incompatible substances. Keep container tightly closed when not in use

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

### SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general **Engineering Controls:** 

ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance

of the personal protective equipment.

Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166. Eye/Face Protection:

Skin Protection Description: Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be

used to prevent contact with eyes, skin or clothing.

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be

permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety

shower

PPE Pictograms:



#### Dipropylene glycol monomethyl ether:

Guideline ACGIH: Skin: Yes.

TLV-STEL: 150 ppm TLV-TWA: 100 ppm

PEL-TWA: 100 ppm PEL-STEL: 150 ppm

Skin: Yes.

Titanium dioxide:

Guideline OSHA:

TLV-TWA: 10 mg/m3 Guideline ACGIH:

Talc, Magnesium silicate hydrate:

Guideline ACGIH: TLV-TWA: 1 mg/m3 Respirable fraction (R)

Guideline OSHA: PEL-TWA: 20 mppcf

#### SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

Physical State: Liquid. Color: White Odor: Slight.

Not applicable. Odor Threshold: **Boiling Point:** >99°F (>37°C) Melting Point: Not applicable.

Density: 11.5

Solubility: Not applicable. Vapor Density: Not applicable. Not applicable. Vapor Pressure: Evaporation Rate: Not applicable. 7 - 10

pH: Viscosity: 50-140

Coefficient of Water/Oil Distribution

Not applicable.

Flammability:

Not applicable.

Flash Point: None. **VOC Content:** 64

### SECTION 10: STABILITY and REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.

Hazardous Polymerization:

Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F. Conditions to Avoid:

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

# SECTION 11: TOXICOLOGICAL INFORMATION

## Dipropylene glycol monomethyl ether:

Administration into the eye - Rabbit Standard Draize test: 500 mg/24H [Mild] (RTECS)

Skin: Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: 10 mL/kg [Details of toxic

effects not reported other than lethal dose value] (RTECS)

Ingestion: Oral - Rat LD50 - Lethal dose, 50 percent kill: 5400 uL/kg [Details of toxic effects not reported other

than lethal dose value]
Oral - Rat LD50 - Lethal dose, 50 percent kill: 5.5 mL/kg [Details of toxic effects not reported other

than lethal dose value] (RTECS)

Titanium dioxide:

Chronic Effects: Causes damage to organs through prolonged or repeated exposure to particulates or powder.

Normal application procedures for this product pose no hazard as to the release of respirable titanium

dioxide dust.

Carcinogenicity: IARC: Group 2B: Possibly carcinogenic to humans. Based on Inhalation studies in rats exposed to fine

or ultrafine particles (dust) of titanium dioxide.

#### SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

### SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal:

Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

# SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Not restricted as a dangerous good.

DOT UN Number: Not restricted as a dangerous good.

IATA Shipping Name: Not restricted as a dangerous good.

IATA UN Number: Not restricted as a dangerous good.

Canadian Shipping Name: Not restricted as a dangerous good.

Canadian UN Number: Not restricted as a dangerous good.

IMDG UN Number: Not restricted as a dangerous good.

IMDG Shipping Name: Not restricted as a dangerous good.

ADR UN Number: Not restricted as a dangerous good.

ADR Shipping Name: Not restricted as a dangerous good.

#### SECTION 15: REGULATORY INFORMATION

### Dipropylene glycol monomethyl ether:

TSCA Inventory Status: Listed
Canada DSL: Listed

Nepheline Syenite:

Canada DSL: Listed

<u>Titanium dioxide</u>:

TSCA Inventory Status: Listed
Canada DSL: Listed

<u>Talc, Magnesium silicate hydrate</u>:

TSCA Inventory Status: Listed
Canada DSL: Listed

# SECTION 16: ADDITIONAL INFORMATION

**HMIS Ratings**:

HMIS Health Hazard: 1
HMIS Fire Hazard: 1
HMIS Reactivity: 0

SDS Creation Date: February 05, 2014
SDS Revision Date: February 29, 2016

Disclaim er:

This Health and Safety Information is correct to the best of our knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, that any revision of this Data Sheet is sent to all customers to whom we have directly supplied this substance, but must point out that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the ultimate user. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Should further information be required, this can be obtained through the sales office whose address is at the top of this data sheet.

Trademark:

The trademarks, service marks, graphics and logos used on this MSDS are registered or unregistered trademarks of BEHR Process Corporation. All Rights Reserved.

Product: KILZ® Adhesion Primer | Manufacturer: | Revison:2/29/2016, Version:0

