



PRODUCT SPECIFICATIONS - TECHNICAL DATA CHART

Physical Construction

Construction	Waterproof Luxury vinyl Tile
Size	6" wide x 36" length (152.4mm x 914.4mm)
Overall Thickness	2.0mm / 0.079 in.
Wear Layer Thickness	0.1mm (4mils)

Packaging

Box	20 planks/box 30 sq.ft/box - 2.79 sqm/box 26.00 Lbs/box - 11.80 kgs/box
Pallet	80 box/pallet 2400 sq.ft/pallet - 233.00 sqm/pallet 2080.00 Lbs/pallet - 944.00 kgs/pallet

Environmental

100% Recycled Material
ISO 9001 Registered Manufacturing Facility

Testing

Dimensional Change	EN ISO 23999:2012	0,03%
Curling		0.0 mm
Residual Indentation	EN ISO 24343-1:2012	0.09mm
Peel Resistance	EN ISO 24345:2012	70N/50mm
Impact Insulation Class (IIC)	ASTM E492-09 / ASTM E989-06	59Db
Reaction to Fire	EN 13501-1:2007	Bfl-s1
Effect of a Castor Chair	EN 425:2002	Pass
Radiant heat energy source	ASTM E648-2017	NFPA 101-2012 Clause 10.2.7

Warranty

Lifetime Limited Residential
15 Years Limited Light Commercial

Installation

Installation Method	Glue Down (Pressure Sensitive Adhesive - Trowel Notch application) Double Sided Heavy Duty Tape - Direct application Construction Adhesive - Chaulk Gun application
---------------------	---

Benefits

Kid proof, Pet friendly, Under-feet comfort, Impact absorption, No acclimation required, For On, Above or Below Grade, Wet moppable. Water-resistance, Surface Tech Guard against spills up to 30 Hours on wet zones.

Notice: The specifications are subject to normal manufacturing variances and are subject to change without notice when technological advancements provide improved product performance and environmental behavior.