

Project:

Fixture Type:

Location:

Contact:

Wish LED

Post Mounted • Wet Location Listed PROGRESS LED

Description:

Wish Collection One-Light LED Post Lantern

Specifications:

- Etched White Linen Glass Cylindrical Diffuser
- · Dimmable to 10% brightness (See Dimming Notes)
- 3.25 in W., 3.5625 in ht., 3.25 in depth
- 6 in of wire supplied

Performance:

Number of Modules	1
Input Power	9 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	623/69.2 (LM-82)
Lumens/LPW (Delivered)	257/32.9 (LM-79)
ССТ	3000 K
CRI	90 CRI
Life (hours)	60000 (L70/TM-21)
EMI/RFI	Meets FCC Title 47, Part 15 Class B
Max. Operating Temp	30 °C
Warranty	5-year Limited Warranty
Labels	cCSAus Wet Location Listed

P6424-3130K9




Dimensions:

Diameter: 9 in Height: 14-13/16 in

Etched White Linen Glass Cylindrical Diffuser

Width: 6 in Height: 7-3/8 in





Wish LED

Post Mounted • Wet Location Listed PROGRESS LED

Dimming Notes:

P6424-3130K9

 ${\sf P6424\text{-}3130K9}\ is\ designed\ to\ be\ compatible\ with\ many\ {\sf ELV/Reverse}\ {\sf Phase}\ controls.$

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron_Nova T NTELV-300

Lutron_Vierti VTELV-600

Lutron_Maestro MAELV-600

Lutron_spacer/system SPSELV-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.