-																							
	M	Α	Т	E	R	I	Α	L	S	Α	F	E	Т	Y	D	Α	Т	Α	S	Н	E	E	T
_																							

	SECTION					
PRODUCT UPC NUM			L PURPOSE FLOO 25228, 25230	R ADHESIVE		
PRODUCT	USE/CLASS	: Floor	Adhesive			
	-	ET	24 HOUR EMERGE TRANSPORTATION MEDICAL	ENCY: DN: 1-800-535-5 : 1-800-327-3	3053 (352-3 874 (513-9	323-3500 558-5111
REVISIO REVISIO	N NO.: 3 N DATE: 01	/05/2000		NFORMATION: 888-DAP-TIPS (
	SECTI	ON 2 - COMPO	SITION/INFORMA	TION ON INGRED	DIENTS	
ITEM		CHEMICAL	NAME	CAS NU	JMBER	WT/WT % RANGE
NO HAZA	RDOUS MATE	RIALS ARE CO	NTAINED IN THI	S PRODUCT.		
	ACG		EXPOSURE LIMIT	'S	COMPANY	SKII
	ACG ACG LV-TWA	TLV-STEL	EXPOSURE LIMIT	'S	COMPANY	SKII
ITEM T	ACG LV-TWA	TLV-STEL for abbrevia	EXPOSURE LIMIT OSE PEL-TWA	'S	COMPANY TLV-TWA	SKII
ITEM T: (See See See Ingredication Communication Communic	ACG LV-TWA ection 16 ents are n cation Sta	TLV-STEL for abbrevia ot considere ndard. e Exposure L	EXPOSURE LIMIT OSE PEL-TWA ation legend) and hazardous per sevels (PEL) ar	'SIA PEL-CEILING	COMPANY TLV-TWA ard	f Labor
ITEM T: (See See See Ingredication Communication Communic	ACG LV-TWA ection 16 ents are n cation Sta Permissibl nal Rule L	TLV-STEL for abbrevia ot considere ndard. e Exposure L imits (CFR 2	EXPOSURE LIMITOSH PEL-TWA Ation legend) Add hazardous per Acevels (PEL) ar Acevels (PEL)	PEL-CEILING The OSHA Haze from the U.S limits may var	COMPANY TLV-TWA ard Dept. of y between	f Labor states.
ITEM T: (See Solution See Solu	ACG LV-TWA ection 16 ents are n cation Sta Permissibl nal Rule L	TLV-STEL for abbrevia ot considere ndard. e Exposure L imits (CFR 2 SECTION 3	EXPOSURE LIMITOUS PEL-TWA PEL-TWA PEL-TWA PEL-TWA PEL	PEL-CEILING The OSHA Haze from the U.S limits may var	COMPANY TLV-TWA ard Dept. of y between this produc	f Labor states.
ITEM T: (See So Ingredic Communic Listed : OSHA Fin	ACG LV-TWA ection 16 ents are n cation Sta Permissibl nal Rule L	for abbrevia ot considere ndard. e Exposure L imits (CFR 2 SECTION 3 SECTION 3	EXPOSURE LIMITOUS PEL-TWA PEL-TWA PEL-TWA PEL-TWA PEL	PEL-CEILING The OSHA Haze of from the U.S limits may var	COMPANY TLV-TWA ard Dept. of y between this produc	f Labor states.
ITEM T: (See See See See See See See See See See	ACG LV-TWA ection 16 ents are n cation Sta Permissibl nal Rule L CY OVERVIE e a signif AL HEALTH	for abbrevia of considere ndard. e Exposure L imits (CFR 2 SECTION 3 W: CAUTION! icant immedi	EXPOSURE LIMITOUSE PEL-TWA Ation legend) Ad hazardous per Acevels (PEL) ar Aceve	PEL-CEILING The OSHA Haze of from the U.S limits may var	COMPANY TLV-TWA ard Dept. of y between chis products	f Labor states.

Product Name: GENERAL PURPOSE FLOOR ADHESIVE Revision Date: 01/05/2000	Page	
SECTION 3 - HAZARDS IDENTIFICATION		į
EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated co with skin may cause irritation.	ntact	1
EFFECTS OF OVEREXPOSURE - INHALATION: Vapor may irritate nose an respiratory tract.	d upper	
EFFECTS OF OVEREXPOSURE - INGESTION: No Information.		
EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Prolonged or repeated contact with skin may cause irritation.		
MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY CONTACT: None know	n.	
PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT INGESTION		- - I
SECTION 4 - FIRST AID MEASURES		
EYE CONTACT: Flush with large quantities of water until irritati subsides. Contact a physician.	on	
SKIN CONTACT: Wash with soap and water.		
INHALATION: Remove to fresh air. Contact a physician immediatel	у.	
INGESTION: DO NOT INDUCE VOMITING. Contact a physician or Regio Control Center immediately.	nal Pois	son
COMMENTS: None.		ı
SECTION 5 - FIRE FIGHTING MEASURES		į
FLASH POINT: >200 F (SETAFLASH CLOSED CUP) LOWER EXPLOSIVE LIMIT UPPER EXPLOSIVE LIMIT		
AUTOIGNITION TEMPERATURE: N.E.		
EXTINGUISHING MEDIA: CO2 DRY CHEMICAL FOAM		
UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.		
SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-conta breathing apparatus pressure-demand (MSHA/NIOSH approved or equiv full protective gear. Use water spray to cool exposed surfaces.		and
SECTION 6 - ACCIDENTAL RELEASE MEASURES		j
SPILL OR LEAK PROCEDURES: Use absorbent material or scrape up dr material and place into containers. (Continued o		3)

Product Name: GENERAL PURPOSE FLOOR ADHESIVE

Revision Date: 01/05/2000 Page 3

SECTION 7 - HANDLING AND STORAGE

HANDLING INFORMATION: KEEP OUT OF REACH OF CHILDREN. Avoid prolonged or repeated contact with skin. Avoid contact with eyes.

STORAGE INFORMATION: Store away from caustics and oxidizers. Keep containers tightly closed when not in use. Keep containers from excessive heat and freezing. Do not store at temperatures above 120 degrees F.

OTHER PRECAUTIONS: Use in a well ventilated area. Provide fresh air such that chemical odors cannot be detected during use and while drying.

ĺ		SECTION	8	_	EXPOSURE	CONTROLS/PERSONAL	PROTECTION

ENGINEERING CONTROLS: Good mechanical ventilation and local exhaust.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. Not required under normal usage and adequate ventilation.

EYE PROTECTION: Safety glasses with side shields recommended.

SKIN PROTECTION: Gloves recommended for repeated or prolonged contact with skin.

OTHER PROTECTIVE EQUIPMENT: None.

HYGIENIC PRACTICES: Although this product is not considered an eye irritant, inhalation hazard, or a skin contact hazard under normal conditions, it is advisable that personnel minimize skin contact, inhalation of vapors, and eye contact. Remove contaminated clothing and wash before reuse.

SECTION	9 –	PHYSICAL	AND	CHEMICAL	PROPERTIES

BOILING RANGE : 210 - 220 F VAPOR DENSITY : Is heavier than air

ODOR : Sweet Odor

APPEARANCE : Off-White EVAPORATION RATE: Is slower than Butyl

SOLUBILITY IN H2O: N.E. Acetate

SPECIFIC GRAVITY : 1.2798

VAPOR PRESSURE : 17.5 mm Hg @ 68F.

PHYSICAL STATE : Paste

(See Section 16 for abbreviation legend)

(Continued on Page 4)

Revision Date: 01/05/2000	Page	4
SECTION 10 - STABILITY AND REACTIVITY		
CONDITIONS TO AVOID: Excessive heat and freezing.		
INCOMPATIBILITY: Strong oxidizers and caustics.		
$\begin{array}{lll} \mbox{\scriptsize HAZARDOUS DECOMPOSITION PRODUCTS:} & \mbox{\scriptsize Normal decompositon products, i.} \\ \mbox{\scriptsize NOx} & \end{array}$	e. CO2	х,
HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.		
STABILITY: This product is stable under normal storage conditions.		
SECTION 11 - TOXICOLOGICAL PROPERTIES		
The toxicological properties of this material are unknown, however, based on the toxicity of its constituents, it is expected to have relatively low toxicity.		
SECTION 12 - ECOLOGICAL INFORMATION		
No Information.		
SECTION 13 - DISPOSAL CONSIDERATIONS		i
WASTE MANAGEMENT/DISPOSAL: Dispose of according to Federal, State, Local Standards. This product does not meet the definition of a hawaste according to U.S. EPA Hazardous Waste Management Regulations, Section 261. State and Local regulations/restrictions are complex differ from Federal regulations. Responsiblity for proper waste diswith the owner of the waste.	and zardou 40 CE and ma	us FR ay
EPA WASTE CODE - If discarded (40 CFR 261): None.		
SECTION 14 - TRANSPORTATION INFORMATION		
DOT PROPER SHIPPING NAME: Not Regulated by D.O.T.		
DOT HAZARD CLASS: NONE		
DOT UN/NA NUMBER: NONE PACKING GROUP: NONE		
(Continued on	Page	5)

Product Name: GENERAL PURPOSE FLOOR ADHESIVE

Product Name: GENERAL PURPOSE FLOOR ADH	ESIVE		
Revision Date: 01/05/2000		Page	
SECTION 15 - REGULATO	RY INFORMATION		İ
U.S. FEDERAL REGULATIONS: AS FOLLOWS -			
OSHA: Hazardous by definition of Hazard 1910.1200)	Communication Standard (29	CFR	
SARA SECTION 313: This product contains the following subs requirements of Section 313 of Title III Reauthorization Act of 1986 and 40 CFR P	of the Superfund Amendmen		
OO SARA Section 313 components exist in	•	RANGE	
TOXIC SUBSTANCES CONTROL ACT: This product contains the following chem reporting requirements of TSCA 12(B) if			
CHEMICAL NAME No information is available.	CAS NUMBER		
NEW JERSEY RIGHT-TO-KNOW: The following materials are non-hazardou components in this product:	s, but are among the top f	ive	
Water Hydrocarbon resin Hydrous Aluminum Silicate Hydrocarbon Oil Calcium Carbonate	CAS NUMBER 7732-18-5 TSRN-807000805128P 1332-58-7 TSRN-618608-5025P 1317-65-3		
PENNSYLVANIA RIGHT-TO-KNOW: The following non-hazardous ingredients greater than 3%:	are present in the product	at	
Water Hydrocarbon resin Carboxylated styrene butadiene Hydrous Aluminum Silicate Calcium Carbonate	CAS NUMBER 7732-18-5 proprietary proprietary 1332-58-7 1317-65-3		
CALIFORNIA PROPOSITION 65: WARNING: The chemical(s) noted below and known to the state of California to caus reproductive harm:			

----- CHEMICAL NAME ----- CAS NUMBER No Proposition 65 chemicals are known to exist in this product.

(Continued on Page 6)

Product Name: GENERAL PURPOSE FLOOR ADHESIVE Revision Date: 01/05/2000 SECTION 15 - REGULATORY INFORMATION |-----| INTERNATIONAL REGULATIONS: AS FOLLOWS -CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings. CANADIAN WHMIS CLASS: No information available. ______ SECTION 16 - OTHER INFORMATION HMIS RATINGS - HEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 0 PREVIOUS MSDS REVISION DATE: 02/01/1997 REASON FOR REVISION: SECTION 1: Address change and new emergency contact phone numbers. VOC LESS WATER, LESS EXEMPT SOLVENTS: 0 grams/ltr VOC MATERIAL : 0 grams/ltr LEGEND: ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS N.A. - NOT APPLICABLE N.E. - NOT ESTABLISHED - PERMISSIBLE EXPOSURE LIMIT PET. - NATIONAL TOXICOLOGY PROGRAM SARA - SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 STEL - SHORT TERM EXPOSURE LIMIT TLV - THRESHOLD LIMIT VALUE(8 HR. TIME WEIGHTED AVERAGE OR TWA) VOC - VOLATILE ORGANIC COMPOUND NJRTK - NEW JERSEY RIGHT TO KNOW LAW

N.D. - NOT DETERMINED

MSDS #77141

This data is offered in good faith as typical values and not as a product specification. No warranty either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review the recommendations in specific context of the intended use and determine if they are appropriate.
