







CATALOG	PAL2412 PAL2412W
	
SPECIFICATION	
Service Voltage	120/240V AC, 1 Phase 3 Wire 208Y/120V AC, 1 Phase 3 Wire
Panelboard Amperage	125A Maximum
Short- Circuit Current Rating	100kA @ 240V AC Maximum
Rated Frequency	60Hz
Enclosure Rating	Indoor (Type 1 - UL50E)
Main Device	Lug
Main Device Rating	125A Maximum
Busbar Rating and Material	125A Aluminum
Branch Circuit Breaker Rating	125A Maximum
Sum of Circuit Breaker Rating	125A Maximum per Stab
Number of Spaces	24 Spaces Maximum
Number of Circuits	48 Circuits Maximum
Standard Listing	UL67 (E21790)
For bottom feed, rotate the entire device by 180°.	
SUITABLE FOR USE AS SERVICE EQUIPMENT	



REPLACEMENT / ACCESSORIES KIT					
TQLFP1	1" Front Filler plates			---	
PTHQLRK2	Circuit Breaker Hold-down kit END			1TQC163000Z0114	
PTHQLRK1	Circuit Breaker Hold-down kit			1TQC163000Z0113	
PD60	Circuit Directory			1TQC163000Z0115	
THP100	Padlocking - THQL			---	
THP100E	Padlocking - AFCI/GFCI			---	
THQLSURGE2	Type 1 plug-on SPD			---	
---	---			---	
---	---			---	
PFAL2412	Front Replacement Kit (Grey)			---	
PFAL2412W	Front Replacement Kit (White)			---	
TDL106	Door Lock Kit			---	
PLTCHGR	Door Handle Gray			1TQC163000Z0116	
---	---			---	
---	---			---	
THLK2125	Subfeed Lug Kit - 125A, 2Pole			---	
PHDWRKIT	P-Series Hardware Kit			1TQC163000Z0123	
---	---			---	
---	---			---	
TORQUE					
Terminal#	Terminal Name	Installed/ Cat.Number	Wire Size	Drive	Torque LB-IN
A & B	Main Lug	Factory Installed	(1) #6-2/0 Cu/Al	Internal Hex	120
N1	Neutral Lug	Factory Installed	(1) #6-2/0 Cu/Al	Internal Hex	120
N7	Neutral Lug	N/A	N/A	N/A	N/A
N2	Neutral Bar	Factory Installed	See Below for Table 1		
N3	Neutral Bar	PNEUXTLG			
N4	Neutral Bar	N/A			
G1	Ground Bar	Factory Installed			
G2	Ground Bar	TGK12/ TGK24			
G3	Ground Bar	TGK12			
G4	Ground Lug	N/A	N/A	N/A	N/A
C & D	Feed Thru Lug	N/A	N/A	N/A	N/A
N5	Ground/ Neutral Lug	TNLK20	(1) #6-2/0 Cu/AL	Internal Hex	120
N6		Factory Installed	(1) #6-2/0 Cu/AL	Internal Hex	120
N5/N6		TNLK250	(1) #1-300 Cu/AL	Internal Hex	200
---	---	---	---	---	---
---	---	---	---	---	---
S	Bonding Screw	N/A	N/A	Slotted/ Robertson	40
When used as service equipment, all unused neutral terminals may be used for equipment ground conductors.					
Table 1 : GROUND/NEUTRAL Bar Terminal Wire size (AWG/KCMIL) & Torque					
Conductor for Ground/Neutral Bar Terminal					
Solid		Stranded		Drive	Torque Lb-In
CU	AL	CU	AL		
(1) 14	-	(1) 14	-	Slotted/ Robertson	15
-	(1) 12	-	(1) 12		15
(1) 12	-	(1) 12	-		20
(1) 10		(1) 10		Robertson	20
-	-	(1) 8			40
-	-	(1) 6-4			45
Multiple Conductor for Ground/Neutral Bar Terminal					
(1) 10 & (1) 12	-	-	-	Slotted/ Robertson	30
(1) 10 & (1) 14	-	(1) 10 & (1) 14	-		30
(2) 10 & (1) 14	-	-	-		30
(1) 12 & (1) 14	-	-	-		30
-	(2) 10 & (1) 12	-	(2) 10 & (1) 12		30
 ReliaHomeTM P - Series					
DRAWING NUMBER		Mod	Rev	Units	
1TQC163300E0016		01	E	Inches	

KNOCKOUTS						
1"-1.25"-1.5"-2"-2.5"	1"-1.25" - 1.5" - 2"	0.75"-1"-1.25"-1.5"	0.5"- 0.75"- 1"	0.5"-0.75"	0.5"	0.281"
X6	X4	X2	X2	X28	X32	X4

		ReliaHome™ P - Series			
DRAWING NUMBER		Mod	Rev	Units	
1TQC163300E0016		01	E	Inches	