

## **Products and Accessories**

### **Sheets and Tiles**

ONDURA Sheets. 48"W. x 79"H.

Corrugated Asphalt Roofing Sheets. Available in 8 colors. Perfect for residential, agricultural, and commercial applications, as well as for re-roofing and small projects. 4.5 sheets per covered square. Matching ridge caps and nails also available.

See page 2 for additional accessories.




**ONDURA Tile.** 48" W. x 19-3/4" H.

These are ONDURA Sheets cut to tile size. Gives the look of clay tile without the weight and cost. 24 tile per covered square. Must be ordered in increments of 4 pieces. Matching ridge tile and nails also available.

See page 2 for additional accessories.



#### **Available Colors-Sheets and Tiles**





# **ONDURA®**

## **Products and Accessories**

### Accessories

Washered Nails. They're galvanized, ring-shanked, painted to match the sheets and come with a large EPDM rubber washer assembled. Standard length is 3", packaged in boxes of 100. The 4" length is recommended for use over rigid insulation or in conjunction with RIDGELINE® Ridge Vent. Stainless steel nails are also available for use in corrosive environments. All nails are available in bulk cartons.



**Ridge Caps.** Available in two widths. Narrow Ridge Caps, ideal for residential use, measure 79" long x 12.5" wide. For farm or commercial use, Wide ONDURA Ridge Caps measure 79" long x 19.25" wide. Both widths are made from the same material as ONDURA sheets and cover 6 feet of ridge or hip with a 7" overlap. Lightweight and easy to install. Use Narrow Ridge Caps with RIDGELINE Ridge Vent.



Closure Strips. Available in two styles: Ventilated or Solid. Use Solid Closure Strips in conjunction with RIDGELINE Ridge Vent. For an improved ventilating system or in areas where additional ventilation is desired use Ventilated Closure Strips. Solid Closure Strips should be used at the ridge, in all valleys and wherever a water-tight seal is necessary. Each closure strip is 44" long; available in packs of four.



**Pipe Flashings.** ONDURA's two pipe flashing accessories install easily with any pipe boot. The accessories have large center areas which accept a wide range of pipe sizes. May be used for hot or cold pipes. Available in two sizes. Small size measures  $20^{\circ}$  W. x  $26^{\circ}$  H.,  $12^{\circ}$  x  $12^{\circ}$  flat center. Large size measures  $28^{\circ}$  W. x  $34^{\circ}$  H.,  $20^{\circ}$  x  $20^{\circ}$  flat center.



RIDGELINE® Ridge Vent. The ideal product for improved air flow throughout the attic area, which helps eliminate moisture, reduce energy costs and increase roof life. What's more, the RIDGELINE Ridge Vent is practically invisible once installed. (Note: 4" ONDURA nails are required to install RIDGELINE Vents with Narrow ONDURA Ridge Caps.)



**Skylights.** Translucent white fiberglass skylight panels, 48" x 79", are not recommended for residential applications, but are an excellent source of natural lighting for agricultural and commercial structures. ONDURA skylights are manufactured with the same dimensions and corrugations as ONDURA sheets. Nail holes must be pre-drilled 1/8" larger than the nail to allow for expansion/contraction. Follow the suggested ONDURA sheet nailing pattern. When one skylight panel overlaps with another, we recommend the use



of a clear mastic such as silicone sealant, and the use of grommet fasteners at side-laps between purlins. When a skylight panel laps with an ONDURA sheet, we recommend the use of rubberized elastomeric flashing cement/caulk.

