

**Model 63 UL Listed Wire Combinations Strip Wire 5/8 in., 7/16 in. for #18 and smaller  
UL File Number E5238**

**Copper to Copper wire only (do not use on aluminum).**



**600 Volt Maximum. For use with solid or stranded combinations**

<b>3 to 6 #14</b>	<b>4 #16 w/ 1 or 2 #14 or #10</b>	<b>5 #14 w/ 1 #18</b>	<b>2 #16 w/ 1 #14 w/ 1 or 2 #12</b>
<b>2 to 6 #12</b>	<b>4 #16 w/ 1 #10</b>	<b>1 #12 w/ 1 or 2 #10</b>	<b>2 #16 w/ 2 #14 w/ 1 #12 or #10</b>
<b>2 to 5 #10</b>	<b>1 #14 w/ 1 to 4 #12</b>	<b>1 #12 w/ 3 #10</b>	<b>2 #16 w/ 1 #12 w/ 1 #10</b>
<b>1 to 2 #8</b>	<b>1 #14 w/ 1 to 3 #10</b>	<b>1 #12 w/ 1 or 2 #8</b>	<b>3 #16 w/ 1 #14 w/ 1 or 2 #12</b>
<b>3 #18 w/3 #16 or #14</b>	<b>1 #14 w/ 1 or 2 #8</b>	<b>1 or 2 #12 w/ 1 or 2 #6</b>	<b>4 # 16 w/ 1 #14 w/ 1 #12 or #10</b>
<b>3 #18 w/1 or 2 #12 or #10</b>	<b>1 or 2 #14 w/ 1 #16</b>	<b>2 #12 w/ 1 or 2 #10</b>	<b>1 #16 w/ 1 #12 w/ 1 or 2 #10</b>
<b>4 #18 w/ 1 or 2 #16, #14, or #12</b>	<b>2 #14 w/ 1 to 4 #12 or #10</b>	<b>2 #12 w/ 1 #8 or #6</b>	<b>1 #14 w/ 1 #12 w/ 1 or 2 #10</b>
<b>5 #18 w/ 1 #16, #14, #12, or #10</b>	<b>2 #14 w/ 1 #18</b>	<b>2 #12 w/ 2 #8</b>	<b>1 #14 w/ 2 #12 w/ 1 #8</b>
<b>1 #16 w/ 2 to 5 #14 or #12</b>	<b>3 #14 w/ 1 to 3 #12 or #10</b>	<b>3 #12 w/ 1 #10 or #8</b>	<b>1 #14 w/ 3 #12 w/ 1 #10</b>
<b>1 #16 w/ 1 to 3 #10</b>	<b>3 or 4 # 14 w/ 1 #18</b>	<b>3 #12 w/ 2 #10</b>	<b>1 #14 w/ 1 #10 w/ 1 #8</b>
<b>2 #16 w/ 1 to 4 #14 or #12</b>	<b>3 #14 w/ 1 #16</b>	<b>4 #12 w/ 1 #10</b>	<b>2 #14 w/ 1 #12 w/ 1 #8</b>
<b>2 #16 w/ 1 or 2 #10</b>	<b>4 #14 w/ 1 or 2 #12 or #10</b>	<b>1 #10 w/ 1 or 2 #8</b>	<b>2 #14 w/ 1 #10 w/ 1 #8</b>
<b>3 #16 w/ 1 to 3 #14</b>	<b>4 #14 w/ 1 #16</b>	<b>1 #8 w/ 1 #16</b>	<b>3 #14 w/ 1 #10 w/ 1 #8</b>
<b>3 #16 w/ 1 or 2 #12 or #10</b>	<b>5 #14 w/ 1 #12 or #10</b>	<b>1 #16 w/ 1 #14 w/ 1 or 2 #12</b>	<b>1 #12 w/ 1 #10 w/ 1 #8</b>