

# AWR-460DB

# 46 Bottle Built-In Compressor Wine Cooler



# **OWNERS MANUAL**

Read and save these instructions.



Manual v1.2

# A Name You Can Trust

Trust should be earned and we will earn yours. Customer happiness is the focus of our business.

From the factory to the warehouse, from the sales floor to your home, the whole NewAir family promises to provide you with innovative products, exceptional service, and support when you need it the most.

#### Count on NewAir.

As a proud NewAir owner, welcome to our family. There are no robots here, real people shipped your product and real people are here to help you.

#### Contact Us:

For questions regarding your product, please contact us at:

Call: 1-855-963-9247

Email: support@newair.com
Online: www.newair.com

#### Connect with Us:

f facebook.com/newairusa

instagram.com/newairusa

youtube.com/newairusa twitter.com/newairusa

# **READ AND SAVE THESE INSTRUCTIONS.**

# **TABLE OF CONTENTS**

Register Your Product Online	4
Safety Information & Warnings	5
Parts List	
Assembly & Installation	7
Operating Instructions	9
Cleaning & Maintenance	11
Wine Storage Guide	12
Troubleshooting	13
Limited Manufacturer's Warranty	

# **SPECIFICATIONS**

Model No.	AWR-460DB	
Voltage:	110~120V	
CURRENT:	1.2A	
FREQUENCY:	60Hz	
Power Consumption:	140W	
STORAGE CAPACITY:	5.3 Cu. Ft.	
TEMPERATURE RANGE:	40°F - 50°F (upper zone)	
	50°F - 66°F (lower zone)	
CLIMATE CLASS:	T/ST/N/SN	
NET WEIGHT:	104.5 lbs	
UNIT SIZE (W x D x H):	23.7" x 22.6" x 33.6"	

#### **REGISTER YOUR PRODUCT ONLINE**

#### Register Your NewAir Product Online Today!

Take advantage of all the benefits product registration has to offer:



## **Service and Support**

Diagnose troubleshooting and service issues faster and more accurately



#### **Recall Notifications**

Stay up to date for safety, system updates and recall notifications



#### **Special Promotions**

Opt-in for NewAir promotions and offers

Registering your product information online is safe & secure and takes less than 2 minutes to complete:

### register.newair.com

Alternatively, we recommend you attach a copy of your sales receipt below an record the following information, located on the manufacturer's nameplate of the rear of the unit. You will need this information if it becomes necessary to contact the manufacturer for service inquiries.				
Date of Purchase:				
Serial Number:				
Model Number:				

#### SAFETY INFORMATION & WARNINGS



When using any electrical appliance, basic safety precautions must be followed in order to reduce the risk of fire, electrical shock and/or injury to persons or property. Be sure to read all instructions before using this appliance and observe the following safety tips:

Attention: To avoid the risk of child entrapment, do not allow children to operate, play with, or crawl inside the unit. If the unit will not be used for an extended period of time, remove the door and leave the shelves in place so that children cannot crawl inside. Also remove the door when disposing of the unit.



## **Shock Hazard – Electrical Grounding Required**

- Never attempt to repair or perform maintenance on the unit until the electricity has been disconnected.
- Never remove the round grounding prong from the plug and never use a two-prong grounding adaptor.
- Altering or cutting of power cord, removal of power cord, removal of power plug, or direct wiring can cause serious injury, fire, and loss of property and/or life, and will void the warranty.
- Never use an extension cord to connect power to the unit.
- Avoid operating this wine cooler in excessively moist or humid environments.



# **Important Precautions:**

- Do not lift unit by door handle.
- Never install or operate the unit inside cabinets or without proper clearances.
- Failure to clean the condenser every six months can cause the unit to malfunction.
- Allow unit temperature to stabilize for 24 hours before use.
- Do not block any internal fans.
- Keep the wine cooler away from hazardous materials or combustible/flammable substances.
- Use only genuine supplier's replacement parts. Imitation parts can damage the unit, affect its operation or performance, and may void the warranty.


#### **PARTS LIST**

When you receive your unit, carefully remove the exterior and interior packaging. It is recommended that you retain the packaging for future use.

Check to make sure the following parts are included:

- 5 Shelves
- Door handle and 2 screws
- 1 instruction manual

#### PARTS DIAGRAM



- Upper zone NTC point
- 2. Upper zone Light
- 3. Upper zone Fan
- 4. Light switch
- 5. Lower zone temperature
- 6. Exhaust window
- 7. Upper zone temperature

- 8. Temperature switch
- 9. Temperature display
- 10. Lower zone NTC point
- 11. Lower zone Fan
- 12. Lower zone Light

- 13. Shelf
- 14. Exhaust window
- 15. Exhaust window
- 16. Foot
- 17. Glass
- 18. Door seal
- 19. Handle
- 20. Lower Hinge
- 21. Lock

#### **ASSEMBLY & INSTALLATION**

#### HANDLE ASSEMBLY

**Tools Required for Assembly:** Phillips screwdriver (not included)

Estimated Assembly Time: 5 minutes

Before installation, attach the handle to the front of the unit with the included screws. It may be necessary to push aside the rubber seal on the inside of the door to reveal the screw holes.

**Caution:** Avoid over-tightening the screws, or you may cause damage to the unit.

#### INSTALLATION



Before connecting the appliance to a power source, let it stand upright for approximately 2 hours. This will reduce the possibility of a malfunction in the cooling system from handling during transportation.

This appliance can either stand alone or be built in. The front grille must be unobstructed.

Before operating your wine cooler for the first time, follow these steps:

- Clean the interior surface of the unit with lukewarm water and a soft cloth.
- Place the cooler on a level surface that will be strong enough to support the unit when it is fully loaded. To level your cooler, adjust the front feet located at the bottom of the unit.
- Install the cooler away from direct sunlight and heat sources such as stoves, heaters, or radiators. Direct sunlight may affect the unit's acrylic coating, and nearby heat sources can increase electrical consumption. Extreme cold or hot ambient temperatures may also prevent proper performance.


#### REVERSING THE DOOR SWING

The door hinge is on the left side by default. If you wish to reverse the swing so that the door opens from the right, it is important to have at least one other person to help. It is dangerous to try to reverse the door swing by yourself.

- 1. Unscrew the upper door hinge while the second person supports the door.
- 2. Remove the upper hinge and carefully lift the door off the bottom hinge.
- 3. Unscrew the bottom hinge and install it on the left side of the unit.
- 4. Flip the door around so that the handle is on the right side and slip the door over the bottom hinge.
- 5. Reattach the door by screwing the top hinge into the holes provided on the upper left surface of the unit. Make adjustments as necessary to be sure the door is aligned properly.

#### OPERATING INSTRUCTIONS

#### HOW TO USE THE BUTTONS ON THE DISPLAY PANEL





Select Celsius or Fahrenheit temperature scale.



Raise the desired temperature.\*




Turn the light on and off.



Lower the desired temperature. \*

- \* To set the upper zone temperature, press the UP or DOWN button on the left side of the control panel. The interior temperature of the upper zone can be adjusted in increments of 1 degree between 40°F and 50°F (5° 10°C).
- \* To set the lower zone temperature, press the UP or DOWN button on the right size of the control panel. The interior temperature of the lower zone can be adjusted in increments of 1 degree between 50°F and 66°F (10° 18°C).

#### THE DISPLAY SCREEN



- Indicates the working status of the entire unit
- 2. Indicates the working status of the lower zone
- 3. Shows set temperature of the lower zone
- 4. Celsius or Fahrenheit degrees
- 5. Actual temperature of the lower zone
- 6. Celsius or Fahrenheit degrees
- 7. Lower Zone

- 8. Celsius or Fahrenheit degrees
- 9. Upper Zone
- 10. Actual temperature of the upper zone
- 11. Indicates the working status of the upper zone
- 12. Shows set temperature of the upper zone
- 13. Celsius or Fahrenheit degrees
- 14. Indicates status of the internal light (on/off)

#### **Working Status Icons:**



Cooling

Maintaining current temperature



Heating

#### **CLEANING & MAINTENANCE**

#### CLEANING YOUR COOLER

#### To clean your cooler:

- Unplug the cooler and remove anything inside.
- Wash the inside of the unit with a solution made of warm water and baking soda solution (2 tablespoons of baking soda to one quart of water).
- Unscrew the water reservoir at the bottom of the unit and rinse with water.
- To clean the outside of the unit, use a mild detergent and warm water.

#### MOVING YOUR COOLER

#### To move your cooler:

- Remove anything stored inside.
- Securely tape down all loose parts located inside the unit.
- Turn the leveling feet up to the base in order to avoid damage.
- Tape the door shut.
- Be sure the cooler stays in an upright position during transportation.

#### WINE STORAGE GUIDE

- The ideal temperature for storing red or white wines is 55°F, with humidity between 60% and 75% RH.
- Store corked bottles on their sides, to keep the cork from drying out and allowing air into the bottle.
- UV rays make wine age faster, so keep bottles out of direct sunlight.
- Avoid heavy vibrations from motors, etc.
- Store wine separately from strong odors that might contaminate the flavor of the wine.

#### HOW LONG SHOULD I STORE MY WINE?

While most wines today are meant to be drunk "young" (within a few years of production) some fine wines are best served by proper aging. But aging too long can decrease the flavor of the wine. Generally speaking, red wines can age longer than white wines, but here is a storage guide for some popular vintages.

Cabernet Sauvignon	7-10 years
Pinot Noir	5 years
Merlot	3-5 years
Zinfandel	2-5 years
Beaujolais	Drink now
Chardonnay	2-3 years
Riesling	3-5 years
Sauvignon Blanc	18 months – 2 years
Pinot Gris	1-2 years
Champagne	Ready to drink

# **TROUBLESHOOTING**

Problem	Possible Causes	Solution
Wine cellar does not	The unit may be	Check if using the wrong
operate.	plugged in using a different voltage.	voltage.
	The circuit breaker may be tripped or there is a blown fuse.	Reset the circuit breaker or check for a broken fuse
Wine cellar is not cold	The external	Lower the temperature
enough.	environment may require a higher setting.	of the cooler.
	The door may be	Open the door less
	opened too frequently.	frequently.
	The door is not closed completely.	Make sure the door is closed securely.
	The door seal does not	Replace the seal on the
	seal properly.	door. Replacements can
		be acquired from the manufacturer.
	The front grille is	Make sure nothing is
	obstructed.	blocking the front grille.
The light does not	There may be a	Contact the
work.	problem with the	manufacturer.
	display board.	
The cooler vibrates	The unit is not sitting	Make sure the unit's
while operating.	on a level floor, or the	feet are in the proper
	unit's feet are not	position and tightened
	correctly installed.	securely.
The cooler produces a lot of noise.	The unit is not leveled.	See above.
	The fan may be	Check the fan to make
	obstructed	sure there is no debris
		or obstruction. If not,
		contact the
_, ,		manufacturer.
The door will not close properly.	The unit is not leveled.	See above.

Problem	Possible Causes	Solution
	The door is not	Check the door hinges
	properly installed.	to make sure they are
		properly installed.
	The seal is weak.	Replace the seal on the
		door.
		Replacements can be
		acquired from the
		manufacturer.
	The shelves are out of	Make sure the shelves
	position.	slide all the way into the
		unit.
The LED display does	There may be a	Contact the
not work.	problem with the main	manufacturer.
	control board.	
	There is a problem with	Contact the
	the plug.	manufacturer.
There is an LED	The cooling kit is no	Contact the
display error, or the	longer working	manufacturer.
LED displays "LO".	properly.	
	The PC Board is faulty.	Contact the
		manufacturer.
The buttons do not	The temperature	Contact the
function.	control panel may be	manufacturer.
	damaged.	

#### LIMITED MANUFACTURER'S WARRANTY

This appliance is covered by a limited manufacturer's warranty. For one year from the original date of purchase, the manufacturer will repair or replace any parts of this appliance that prove to be defective in materials and workmanship, provided the appliance has been used under normal operating conditions as intended by the manufacturer.

#### Warranty Terms:

During the first year, any components of this appliance found to be defective due to materials or workmanship will be repaired or replaced, at the manufacturer's discretion, at no charge to the original purchaser. The purchaser will be responsible for any removal or transportation costs, if needed.

#### **Warranty Exclusions:**

The warranty will not apply if damage is caused by any of the following:

- Power failure
- Damage in transit or when moving the appliance
- Improper power supply such as low voltage, defective household wiring or inadequate fuses
- Accident, alteration, misuse or abuse of the appliance such as using non-approved accessories, inadequate air circulation in the room or abnormal operating conditions (extreme temperatures)
- Use in commercial or industrial applications
- Fire, water damage, theft, war, riot, hostility or acts of God such as hurricanes, floods, etc.
- Use of force or damage caused by external influences
- Partially or completely dismantled appliances
- Excess wear and tear by the user

Replacement parts and/or units will be new, re-manufactured or refurbished and is subject to the manufacturer's discretion. For technical support and warranty service, please email <a href="mailto:support@newairusa.com">support@newairusa.com</a>.