



POWERMATIC®



**THIS WILL
CHANGE
THE WAY
YOU WORK.**

NEW ARMORGLIDE TECHNOLOGY

LOW FRICTION | RUST RESISTANT | MAINTENANCE FREE | DURABLE COATING | ENHANCED VISIBILITY

A close-up photograph of a yellow and black industrial machine, likely a table saw or jointer. A black protective rail or guard is in the foreground, partially obscuring the view. The background is blurred, showing more of the yellow machine and a wooden structure.

Introducing ArmorGlide

This low-friction, industrial-grade coating on Jointers, Table Saws, and Bandsaws is rust resistant, requires less maintenance, and gives you more control. ArmorGlide empowers you to spend more time doing what you love rather than wasting time maintaining a table.



LOW FRICTION

ArmorGlide tables require 50% less force, so you get more control.



ENHANCED VISIBILITY

The dark surface reduces glare, so you can see where you're cutting better.



MAINTENANCE FREE

Get rid of the waxes and messy cleaning supplies; do more of what you love.



DURABLE COATING

ArmorGlide tables can withstand 250,000 passes without showing signs of wear.



RUST RESISTANT

Ditch the steel wool and never worry about rust again.



BANDSAWS

NEW ARMORGLIDE TECHNOLOGY



LOW FRICTION



RUST RESISTANT



MAINTENANCE FREE



DURABLE COATING



ENHANCED VISIBILITY

MODEL NUMBER	PM1500T	PM1800BT	PM1800B-3T	PM2013BT	PM2013B-3T	PM2415BT	PM2415B-3T
Stock Number	PM1-1791500T	PM1-1791800BT	PM1-1791801BT	PM1-1791257BT	PM1-1791258BT	PM1-1791259BT	PM1-1791260BT
Cutting Capacity Width (Throat) (In.)	14½	18	18	20	20	24	24
Cutting Capacity Height (In.)	14	18	18	18	18	15	15
Table Type	ArmorGlide	ArmorGlide	ArmorGlide	ArmorGlide	ArmorGlide	ArmorGlide	ArmorGlide
Motor Power (HP)	3	5	5	5	5	5	5
Motor Phase (PH)	1	1	3	1	3	1	3
Motor Voltage (V.)	230	230	230/460*	230	230/460*	230	230/460*
Prewired Voltage (V.)	230	230	230	230	230	230	230
Blade Length (In.)	153	160	160	170	170	183	183
Table Height from Floor (In.)	40	38	38	36	36	35	35
Dust Port Outside Diameter (In.)	4	4	4	4	4	4	4

*PLEASE CONTACT CUSTOMER SERVICE AT 1-800-274-6848 WITH ANY REQUESTS FOR 460V MACHINES



LEARN MORE BY SCANNING QR CODE OR
VISITING WOOD.POWERMATIC.COM/ARMORGLIDE



JOINTERS

NEW ARMORGLIDE TECHNOLOGY



LOW FRICTION



RUST RESISTANT



MAINTENANCE FREE



DURABLE COATING



ENHANCED VISIBILITY

MODEL NUMBER	PJ882T	PJ-882HHT	1285T JNTR	1285T JNTR HH	1285T JNTR HH	PJ1696T JNTR HH
Stock Number	PM1-1610079T	PM1-1610082T	PM1-1791241T	PM1-1791307T	PM1-1791308T	PM1-1791283T
Cutting Capacity (W x D) (In.)	8 x ½	8 x ½	11¾ x ¾	11¾ x ¾	11¾ x ¾	16 x ¾
Type of Cutterhead	Straight Knife	Helical	Straight Knife	Helical	Helical	Helical
Table Type	ArmorGlide	ArmorGlide	ArmorGlide	ArmorGlide	ArmorGlide	ArmorGlide
Motor Power (HP)	2	2	3	3	3	7½
Motor Phase (PH)	1	1	1	1	3	3
Motor Voltage (V.)	230	230	230	230	230/460*	230/460*
Prewired Voltage (V.)	230	230	230	230	230	230
Infeed Table Length (In.)	44	44	39	39	39	47½
Cutterhead Speed (RPM)	7000	7000	5000	5000	5000	5200
Recommended Circuit Size (Amps.)	20	20	30	30	10	25

*PLEASE CONTACT CUSTOMER SERVICE AT 1-800-274-6848 WITH ANY REQUESTS FOR 460V MACHINES



LEARN MORE BY SCANNING QR CODE OR
VISITING WOOD.POWERMATIC.COM/ARMORGLIDE



TABLE SAWS

NEW ARMORGLIDE TECHNOLOGY



LOW FRICTION



RUST RESISTANT



MAINTENANCE FREE



DURABLE COATING



ENHANCED VISIBILITY

MODEL NUMBER	PM1000T AF	PM1000T 52" AF	PM2000T 30" RIP	PM2000T 50" RIP	PM2000T 50" RIP WB	PM2000T 50" RIP RL	PM2000T 30" RIP	PM2000T 50" RIP
Stock Number	PM1- 1791000KT	PM1- 1791001KT	PM1- PM23130KT	PM1- PM23150KT	PM1- PM23150WKT	PM1- PM23150RKT	PM1- PM25130KT	PM1- PM25150KT
Max Rip Right (In.)	30	52	30	50	50	50	30	50
Blade Diameter, Arbor (In.)	10, 5/8	10, 5/8	10, 5/8	10, 5/8	10, 5/8	10, 5/8	10, 5/8	10, 5/8
Table Type	ArmorGlide w/ Extension Table	ArmorGlide w/ Extension Table	ArmorGlide w/ Extension Table	ArmorGlide w/ Extension Table	ArmorGlide w/ Workbench Table	ArmorGlide w/ Router Lift	ArmorGlide w/ Extension Table	ArmorGlide w/ Extension Table
Motor Power (HP)	1 3/4	1 3/4	3	3	3	3	5	5
Motor Phase (PH)	1	1	1	1	1	1	1	1
Motor Voltage (V.)	115/230	115/230	230	230	230	230	230	230
Prewired Voltage (V.)	115	115	230	230	230	230	230	230
Overall Dimensions (L x W x H) (In.)	43 x 61 x 44	43 x 83 x 44	66 3/4 x 39 1/8 x 40 3/8	84 3/4 x 39 1/8 x 40 3/8	84 3/4 x 39 1/8 x 40 3/8	84 3/4 x 39 1/8 x 40 3/8	66 3/4 x 39 1/8 x 40 3/8	84 3/4 x 39 1/8 x 40 3/8
Table Height from Floor (In.)	34 1/4	34 1/4	35	35	35	35	35	35
Max Rip Left (In.)	12	12	13 1/2	13 1/2	13 1/2	13 1/2	13 1/2	13 1/2



LEARN MORE BY SCANNING QR CODE OR
VISITING WOOD.POWERMATIC.COM/ARMORGLIDE



TABLE SAWS

NEW ARMORGLIDE TECHNOLOGY



LOW FRICTION



RUST RESISTANT



MAINTENANCE FREE



DURABLE COATING



ENHANCED VISIBILITY

MODEL NUMBER	PM2000T 50" RIP WB	PM2000T 50" RIP RL	PM2000T 30" RIP	PM2000T 50" RIP	PM2000T 50" RIP WB	PM2000T 50" RIP RL	PM3000T 50" RIP
Stock Number	PM1- PM25150WKT	PM1- PM25150RKT	PM1- PM25330KT	PM1- PM25350KT	PM1- PM25350WKT	PM1- PM25350RKT	PM1- PM375350KT
Max Rip Right (In.)	50	50	30	50	50	50	50
Blade Diameter, Arbor (In.)	10, 5/8	10, 5/8	10, 5/8	10, 5/8	10, 5/8	10, 5/8	14, 1
Table Type	ArmorGlide w/ Workbench Table	ArmorGlide w/ Router Lift	ArmorGlide w/ Extension Table	ArmorGlide w/ Extension Table	ArmorGlide w/ Workbench Table	ArmorGlide w/ Router Lift	ArmorGlide w/ Extension Table
Motor Power (HP)	5	5	5	5	5	5	7½
Motor Phase (PH)	1	1	3	3	3	3	3
Motor Voltage (V.)	230	230	230/460*	230/460*	230/460*	230/460*	230/460*
Prewired Voltage (V.)	230	230	230	230	230	230	230
Overall Dimensions (L x W x H) (In.)	84¾ x 39½ x 40¾	84¾ x 39½ x 40¾	66¾ x 39½ x 40¾	84¾ x 39½ x 40¾	84¾ x 39½ x 40¾	84¾ x 39½ x 40¾	84⅞ x 46½ x 42¾
Table Height from Floor (In.)	35	35	35	35	35	35	35¼
Max Rip Left (In.)	13½	13½	13½	13½	13½	13½	14

*PLEASE CONTACT CUSTOMER SERVICE AT 1-800-274-6848 WITH ANY REQUESTS FOR 460V MACHINES



LEARN MORE BY SCANNING QR CODE OR
VISITING WOOD.POWERMATIC.COM/ARMORGLIDE



POWERMATIC®

NEW ARMORGLIDE TECHNOLOGY

LOW FRICTION | RUST RESISTANT | MAINTENANCE FREE | DURABLE COATING | ENHANCED VISIBILITY



LEARN MORE BY SCANNING QR CODE OR
VISITING WOOD.POWERMATIC.COM/ARMORGLIDE