

SQR73105WH

X Series 15A 500W Single Pole Occupancy/
Humidity Sensor Light & Fan Control Back Wires
Matte White



Main

Range	Square D X Series
Product or Component Type	Sensor
Device Application	Control
Device presentation	Mechanism with fixing frame
Aesthetic name	X Series
Number of gangs	1 gang
Number of poles	1

Complementary

Switch Function	1-way
Sensor Type	PIR Humidity sensor Light level sensor
[Ie] rated operational current AC	10 A
[Ue] rated operational voltage	120 V
Network type	AC
Network Frequency	60 Hz
Load type	Halogen 0...500 W Incandescent 0...500 W Dimmable LED 0...150 W Fan motor 2.5 A
Maximum Horse Power Rating	0.25 Hp
Mounting Mode	By screws
Device mounting	Flush
Material	Plastic: strap Metal fixing frame
Color	White
Surface Finish	Matt
Marking	LIGHT-FAN
Width	1.69 In (43 mm)
Height	4.06 In (103 mm)
Quantity per Set	1 piece

Environment

Product Certifications	CULus ICES-003
Standards	UL 1917

Ordering and shipping details

GTIN	785901549734
Nbr. of units in pkg.	1
Package weight(Lbs)	6.10 Oz (173 g)

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	4.17 In (10.6 cm)
Package 1 width	2.44 In (6.2 cm)
Package 1 Length	2.56 In (6.5 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	1920
Package 2 Weight	884.13 Lb(US) (401.035 kg)
Package 2 Height	47.24 In (120 cm)
Package 2 width	39.37 In (100 cm)
Package 2 Length	47.24 In (120 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: carbon-black, which is known to the State of California to cause cancer, and Bisphenol A (B-PA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	2 year
----------	--------

Product Life Status : **Commercialised**