

# Hisense

**22 PINTS**  
DOE Test Procedure,  
10 CFR part 430, subpart B, appendix X

**30 PINTS**  
DOE Test Procedure,  
10 CFR part 430, subpart B, appendix X

**DEHUMIDIFIER** EASY CONTROL  
up to 700 sq.ft. coverage

**DH3019K1W**



- Bucket full indicator avoids overflows
- Simple manual operation, and unit will run continuously if the desired humidity is set to 30%.
- Single Fan Speed
- Low-temperature Operation (38°F)



#### Low Noise Airflow System

High performance centrifugal fan ensures quiet operation with just 45dB(A).



#### Energy Efficient

Energy Star means its more energy efficient and helps reduce your utility bill.



#### Filter Indicator

Washable filter helps to reduce bacteria, odors and particles.



#### Warranty

2 Years Parts & Labor.

## Control Humidity - Helps keep your home conveniently dry, fresh, and quiet

The Hisense DH3019K1W Energy Star 30\* Pint Single Speed Dehumidifier quietly collects water into the slide-out internal bucket, or can discharge the water via connecting a garden hose (not included) through the side of the cabinet. Reliable and eco-friendly this dehumidifier can operate at temperatures as low as 38°F. Easy control and the very low sound level make this a versatile choice. Additional features include an adjustable humidistat, easy accessible and washable filter, and full-tank alert.

## TECHNICAL SPECIFICATIONS

### Performance

Hisense-Model	DH3019K1W
Dehumidification (Pints / 24 hours)	30*
Dehumidification (Pints / 24 hours)	22**
Heating Capacity	N/A
Coverage	Up to 700 sq. ft.
Refrigerant	R-410A
Noise Level in dB(A)	45 dB(A)

### Electrical

Voltage / Freq / Amps	115V / 60Hz, 2.7A* / 2.4A**
-----------------------	-----------------------------

### General Features

Unit Control Type	Electronic
Fan Control	Button
Adj. Humidity Control	N/A
Display Type	LED
Continuous Run	N/A
Auto Dry	N/A
Manual Setting	30% ~ 80%
Timer-Clock	N/A
Fan Speeds	Single Fan Speed
Pump Mode	No

### General Features

Auto Bucket Shutoff	Yes
Bucket Capacity	8.5 pints
Bucket Shutoff Capacity	7.0 pints
Garden Hose Connection	Yes - garden hose not included
Washable Filters	Yes
Max Pump Discharge Height	N/A

### Accessories

Quick Connect Hose	No
--------------------	----

### Approvals

Safety	UL
Energy	Energy Star

### Shipping

Unit Dimension WxDxH (mm)	334 x 218 x 505
Carton Dimension WxDxH (mm)	380 x 266 x 535

Net Weight / Gross Weight (Kg)	12.8 / 14.0
Unit Dimension WxDxH (inch)	13.2 x 8.6 x 19.9
Carton Dimension WxDxH (inch)	15.0 x 10.5 x 21.1
Net Weight / Gross Weight (lbs)	28.2 / 30.0
Loading (40HQ)	1358
Loading (53')	1248 (floor loaded)
<b>Product</b>	
Parts & Labor	2 years
UPC	00819130023656

Note:

\* : DOE Test Procedure 10 CFR part 430, subpart B, appendix X1;

\*\* : DOE Test Procedure 10 CFR part 430, subpart B, appendix X1;



Control Panel



Gravity Draining with Garden Hose (not included)

All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise.

©2019 Hisense USA, All rights reserved

Hisense USA Corporation  
7310 McGinnis Ferry Road, Suwanee, GA, 30024  
1-877-465-3566  
www.hisense-usa.com

