

# QC CL-5400 RF QuietCool Original Classic Line

## QC CL-5400 RF Specifications

Airflow	Hi: 5,024 CFM / Low: 4,406 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 3,950 CFM / Low: 3,240 CFM	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,675 SQFT to 2,512 SQFT	
Energy Use	Hi: 634 Watts / Low: 525 Watts	
Amps	Hi: 5.60 / Low: 4.55	
Motor Voltage	120 VAC, 60 Hz	
# of Speeds	2	
dBA	Hi: 51.2 / Low: 45.7	
Minimum Attic Clearance	38"	
Duct Diameter	20"	
Duct Length	9 feet	
Motor Head Diameter	20 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Included IT-36003 QuietCool Wireless RF Control Kit with Glass Wireless RF Switch	
Warranty	10 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	6.7 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 30 1/4"	
Removable Grille Outside Dimension	16" x 32"	
Shipping Weight	75 lbs.	
Box Dimensions	39" x 24" x 39"	
In The Box	<div> -QC CL-5400 Motorhead  -Ceiling Grille  -Cut-out Template  -Window Locks </div> <div> -Damper Box  -9 Foot Duct  -Accessory Bag  -Wireless RF Control Kit </div>	



For more information, visit our website at:  
**QUIETCOOLSYSTEMS.COM**