



ALL PURPOSE 3006 ULTRA®

Siliconized Acrylic Latex Elastomeric Sealant

White Lightning® 3006 Ultra is a high-performance Siliconized Acrylic Latex Elastomeric Sealant ideal for interior and exterior applications. It's formulated for filling joints where more movement is expected. White Lightning 3006 Ultra seals cracks between drywall, wood, glass, masonry, concrete, metal, porcelain and plastic.

- Excellent Flexibility – 70% Total Joint Movement
- Durable and Crack Resistant
- Superior Adhesion
- Cured Sealant is Mold and Mildew Resistant



WATERPROOF



PAINTABLE



INTERIOR/
EXTERIOR



WATER
CLEANUP



PART #	UPC	COLOR	SIZE
W11000010	0-23275-14761-4	White	10 fl. oz.
W11000005	0-23275-52493-4	White	5.5 fl. oz.
W11001010	0-23275-14762-1	Clear	10 fl. oz.
W11001005	0-23275-52494-1	Clear	5.5 fl. oz.
W11004010	0-23275-03068-8	Gray	10 fl. oz.
W11005010	0-23275-03069-5	Black	10 fl. oz.
W11002010	0-23275-03070-1	Almond	10 fl. oz.
W11006010	0-23275-03071-8	Cedar	10 fl. oz.





ALL PURPOSE 3006 ULTRA®

Physical Properties:

Type: Acrylic

Colors: White, Clear, Gray, Black, Almond, Cedar

Shelf Life: 24 Months

Flash Point: n/a (water based)

Flammability: n/a (water based)

Full Cure Time: 5 to 7 days at 75 °F

Tack Free Time: 10 Minutes at 75 °F

Application Temperature: above 40 °F

Service Temperature: -30 °F to 180 °F

Vehicle: Water

Solids by Weight: 81.3% +/- .2%

Weight/Gallon: 12.67 +/- 0.2 lbs/gal

Painting: Paintable

Primers: Not required

Mildew Resistance: Excellent

Water Resistance: Good

Odor: Low

Shrinkage: Low

Performance Data:

Joint Size: 1/8" x 1/8" to 1/2" x 1/2"

Freeze-Thaw Stability: Passes Through 5 Cycles

Shelf Life: 24 Months

Cleanup: Water; promptly clean tools and excess caulk with water or a damp cloth.

Flexibility: Excellent; 70% Total Joint Movement

Linear Coverage 10 oz. cartridge 24' at 1/4" wide by 1/4" deep bead; 5.5 oz. squeeze tube 12' at 1/4" wide by 1/4" deep bead

Painting: A minimum of 2 hours dry time is required before painting with latex- or oil-based paint. Allow extra dry time during periods of high humidity and/or cool temperatures.

NOTE: Acrylic Clear will apply appearing milky white and dry clear when fully cured.

ASTM:

Exceeds ASTM C-920, Class 35. Exceeds performance requirements of Federal Specification TT-S-00230C Type II Class A. Tested at Riverbank Acoustical Laboratories in accordance with ASTM E90 and C-919, this product was sound tested and proven to be an integral component in maintaining STC/MTC partition ratings. It has also been tested in accordance with ASTM C-287 and D-217.

White Lightning® 3006 Ultra® has achieved GREENGUARD Gold Certification.

Application:

1. Remove all existing caulk.
2. Clean thoroughly to remove all loose material, grease, dirt, oil, wax, loose paint, dust and soap film.
3. Remove mold/mildew with bleach (4:1 mix, water to bleach) and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

10 oz. Cartridge

- Cut nozzle tip at a 45° angle.
- Load cartridge into caulk gun.
- Squeeze trigger to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

5.5 oz. squeeze tube

- Remove cap, cut tube tip at a 45° angle.
- Squeeze tube to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool

Cleanup:

Water; promptly clean tools and excess caulk with water or a damp cloth.

Cautions:

See SDS.

Limitations:

For best results, apply at temperatures above 40 °F and allow 24 hours to cure before exposing to moisture. Do not apply to frozen or frost-covered surfaces. Not for use below grade, on aquariums or for marine use below the water line.

LIMITED WARRANTY:

This warranty is made to you, the property owner purchaser, and is only transferable by a contractor, if the contractor purchased and applied the product to the property for you. If the product fails to perform in accordance with applicable product literature for as long as you own the property, White Lightning shall either replace an equivalent quantity of product free of charge or refund the original purchase price upon presentation of proof of purchase. For a replacement or a refund, please visit the store where the product was purchased or contact customer service at 1-800-241-5295. This warranty shall not apply to any defect, damage or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application of the product. Your exclusive remedy, and White Lightning's sole liability under this warranty is the replacement of product or refund by White Lightning and does not include labor or costs associated with the application or removal of any product. **IN NO EVENT SHALL WHITE LIGHTNING BE LIABLE FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE, OR INDIRECT DAMAGES WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE LIMITED TO A ONE-YEAR PERIOD FROM THE DATE OF PURCHASE.** Some states do not allow limitations on how long an implied warranty lasts or limitations on incidental or consequential damages, so portions of the limitations above might not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from state to state.

For more information, please call or write:

White Lightning Products 101 W Prospect Ave., Cleveland, OH 44115
1-800-241-5295 Option 1 Customer Service • 1-800-241-5295 Option 2 Technical Service
wlcaulk.com