2 and 3-wire earth ground resistance measurements

Features:

- Measures earth ground resistance from 20Ω to 2000Ω
- Dual LCD display with backlight
- Multimeter functions: AC/DC Voltage and Resistance
- · Data Hold freezes reading on the display
- Auto power off and low battery indicator
- · Overmolded housing for added durability
- Complete with protective holster, test leads, (2) auxiliary earth rods, (6) AA batteries, and carrying case
- Optional model complete with Certificate of Traceability to N.I.S.T.
- 1 year warranty

Applications:

Specifications
Earth Resistance

Accuracy

Resolution

Earth Voltage

AC/DC Voltage

Safety Category

Dimensions

Resistance

Continuity

Power

Weight

An earth ground is used as a zero-volt reference point for power substations, buildings, communication towers, and as a path to dissipate lightning strikes to prevent damage to them. The NEC (National Electrical Code) requires that a single path to ground should be 25 ohms or less. If it is higher than 25 ohms, you should add an additional ground rod 6 feet away. The Earth Ground ResistanceTester provides an easy way to check this reading in installed systemsor for a good location to install a new system.

20,200, 2000

750ACV/1000VDC

(6) AA batteries

CAT III 1000V

1.5lbs (700g)

±2%

0.01

200V

200k

<40

TRIPLETT EG400 BAT BAS SU HOLD AC DESTRUCTOR DESTRUCTOR







| EG480 | Earth Ground Resistance Tester Kit |
|------------|---|
| EG480-NIST | EG480 Including Certificate of Traceability to N.I.S.T. |

7.8 x 3.6 x 1.9" (200 x 92 x 50mm)



