



Versatility That Beats the Elements (1 Available in Color-Matching Quik Guard[®] Coating Plus, Painted Head Type 316 and Type 305 **Stainless Steel** (800) 999-5099

strongtie.com

For All Types of Composite Decking

The Deck-Drive[™] DCU Composite screw is engineered to provide beautiful fastening results for all types of composite decking while also offering greater ease of installation, a clean finish and superb corrosion resistance. Now there is one go-to-product line for all your composite decking applications, eliminating the need to mix and match screws to the decking they are suited for — or to the environment where the deck is built.

For superior corrosion resistance in marine or high-exposure environments, choose the appropriate stainlesssteel DCU Composite screw (Type 316 or Type 305). They are now available with color-matching painted heads in 11 colors to blend with popular decking manufacturers, and to provide a more concealed professional finish. For medium levels of corrosion resistance, carbon-steel Deck-Drive DCU Composite screws are available in 11 colors of our Quik Guard[®] coating, also matched to blend with most major decking manufacturers.

DCU Composite screws are available in 2³/₄" and 2" lengths for a variety of deck boards and cladding.

These screws are offered in bulk and collated for the Quik Drive® auto-feed screw driving system.

T20 6-lobe recess Tri-lobe thread design reduces Quik Guard coating enables cracking or splitting in the composite reduces cam-out the screw to be used with board during driving, as debris is many preservative-treated automatically extracted wood substrates* DCU COMPOSITE Screw Inverted upper threads clear Double-cut point penetrates even excess material to ensure the the hardest types of composite decking with ease for faster starts screw is seated properly and consistently DCU COMPOSITE SS Screw (Available with color-matching painted heads) Cap head prevents mushrooming and material from rising up above the deck, making for a smoother, clean-looking installation

DCU Corrosion Resistance Table

Decking Screw	Material/ Coating	Environment	Environment Example	Corrosion Resistance Level
DCU COMPOSITE SS	Type 316 Stainless Steel	Coastal/water	Marine and coastal environments, brackish water, severe weather, pool/hot tub areas	Up to severe corrosion resistance
DCU COMPOSITE SS	Type 305 Stainless Steel	Elevated service	Wet areas, freshwater rivers and lakes, moderate weather exposure	Up to high corrosion resistance
DCU COMPOSITE	Quik Guard	Dry service and wet service	Interior and exterior applications, preservative-treated wood	Up to medium corrosion resistance

* Quik Guard coating has been evaluated for use in ACQ-treated wood (0.4 pcf) by Simpson Strong-Tie following ICC-ES AC257. (See **strongtie.com/info** for more information.)

Trex: Deck-Drive DCU Composite screws are approved by Trex[®] for Trex 1" x 6" and 2" x 6" composite decking.



Deck Drive DCU COMPOSITE Screw

For All Types of Composite Decking

Deck-Drive™ DCU Composite screws are engineered to be the fastener of choice for virtually all types of composite-decking products, including wood/plastic composites, encapsulated wood/plastic composites, HDPE (high-density polyethylene). In addition, the DCU SS screw is the ideal solution for PVC decking.

Available in 11 color-matched shades to blend with these leading composite-decking manufacturers' products:

- AZEK[®]
- Clubhouse
- Deckorators[®]
- DuraLife[™]
- EverGrain[®]
- Fiberon®
- Gossen®
- Lumberock[®]
- MoistureShield

• Rhino Deck® TanDeck[™]

- TimberTech[®]
- Trex®
- TUFboard[®]
- Veranda[®] • Wolf®
- And more

For color-matching information, please refer to strongtie.com/deckcolormatch.

AZEK, Deckorators, DuraLife, EverGrain, Fiberon, Gossen, Lumberock, Rhino Deck, TanDeck, TimberTech, Trex, TUFboard, Veranda and Wolf are trademarks of their respective companies.

Carbon Steel, Quik Guard[®] Coating

0.00.00.0	0.000., 0.0.		0000000			
Size	Length (in.)	Color	Bit Size	Retail Pack (70 ct.)	Deck Pack (350 ct.) ¹	Contractor Bucket (1,750 ct.) ²
#10	2	Gray	T20	DCU2GRR70	DCU2GRR350	—
#10	23⁄4	Brown 01	T20		DCU234BR01R350	DCU234BR01MB
#10	23⁄4	Brown 05	T20		DCU234BR05R350	DCU234BR05MB
#10	23⁄4	Gray	T20		DCU234GRR350	DCU234GRMB
#10	23⁄4	Gray 01	T20		DCU234GR01R350	DCU234GR01MB
#10	23⁄4	Gray 04	T20		DCU234GR04R350	DCU234GR04MB
#10	23⁄4	Red	T20		DCU234RDR350	DCU234RDMB
#10	23⁄4	Red 01	T20		DCU234RD01R350	DCU234RD01MB
#10	23⁄4	Tan	T20		DCU234TNR350	DCU234TNMB
#10	23⁄4	Tan 01	T20		DCU234TN01R350	DCU234TN01MB
#10	23⁄4	Tan 02	T20		DCU234TN02R350	DCU234TN02MB
#10	23⁄4	Tan 03	T20		DCU234TN03R350	DCU234TN03MB

1.350 screws install approx. 100 sq. ft. of decking with framing at 16" on-center spacing.

2.1,750 screws install approx. 500 sq. ft. of decking with framing at 16" on-center spacing.

rbon Stee	el, Quik Guard	d Coating (Co	ollated)	•	- 2¾"►
Size	Length (in.)	Color	Bit Size	Model No. (1,000 ct.)	PR0300S
#10	23⁄4	Brown 01	T20	DCU234SBR01	\checkmark
#10	23⁄4	Brown 05	T20	DCU234SBR05	\checkmark
#10	23⁄4	Gray	T20	DCU234SGR	\checkmark
#10	23⁄4	Gray 01	T20	DCU234SGR01	\checkmark
#10	23⁄4	Gray 04	T20	DCU234SGR04	\checkmark
#10	23⁄4	Red	T20	DCU234SRD	\checkmark
#10	23⁄4	Red 01	T20	DCU234SRD01	\checkmark
#10	23⁄4	Tan	T20	DCU234STN	\checkmark
#10	23⁄4	Tan 01	T20	DCU234STN01	\checkmark
#10	23⁄4	Tan 02	T20	DCU234STN02	\checkmark
#10	23/4	Tan 03	T20	DCU234STN03	\checkmark

Car

Type 305 or 316 Stainless Steel, Unpainted (Collated)

Size	Length (in.)	Material	Bit Size	Model No. (1,000 ct.)	PR0300S		
#10	23⁄4	Type 305 stainless steel	T20	DCU234S305	\checkmark		
#10	23⁄4	Type 316 stainless steel	T20	DCU234S316	\checkmark		


Driver bits included in both deck packs and contractor packs (1,750 ct., 1,000 ct.)

T20 6-lobe bit replacement for bulk screws: BIT20T-RC3

T20 6-lobe bit replacement for collated screws: BITTX20-RC10 (10 pack), BITTX20-RC3 (3 pack)



2", 2¾"



SIMPSON Strong-Tie

0

Deck Drive DCU COMPOSITE Screw

For All Types of Composite Decking

Type 305 Stainless Steel, Painted Head

Size	Length (in.)	Color	Bit Size	Deck Pack (350 ct.) ¹	Contractor Bucket (1,750 c
#10	23⁄4	—	T20	DCU234P305	DCU234MB305
#10	23⁄4	Brown 01	T20	DCU234P305BR01	DCU234MB305BR01
#10	23⁄4	Brown 05	T20	DCU234P305BR05	DCU234MB305BR05
#10	23⁄4	Gray	T20	DCU234P305GR	DCU234MB305GR
#10	23⁄4	Gray 01	T20	DCU234P305GR01	DCU234MB305GR01
#10	23⁄4	Gray 04	T20	DCU234P305GR04	DCU234MB305GR04
#10	23⁄4	Red	T20	DCU234P305RD	DCU234MB305RD
#10	23⁄4	Red 01	T20	DCU234P305RD01	DCU234MB305RD01
#10	23⁄4	Tan	T20	DCU234P305TN	DCU234MB305TN
#10	23⁄4	Tan 01	T20	DCU234P305TN01	DCU234MB305TN01
#10	23⁄4	Tan 02	T20	DCU234P305TN02	DCU234MB305TN02
#10	23⁄4	Tan 03	T20	DCU234P305TN03	DCU234MB305TN03

Type 316 Stainless Steel, Painted Head

						, .
Size	Length (in.)	Color	Bit Size	Retail Pack (70 ct.)	Deck Pack (350 ct.) ¹	Contractor Bucket (1,750 ct.) ²
#10	2		T20	DCU2C316	DCU2P316	_
#10	23⁄4		T20		DCU234P316	DCU234MB316
#10	23⁄4	Brown 01	T20	DCU234C316BR01	DCU234P316BR01	DCU234MB316BR01
#10	23⁄4	Brown 05	T20	DCU234C316BR05	DCU234P316BR05	DCU234MB316BR05
#10	23⁄4	Gray	T20	DCU234C316GR	DCU234P316GR	DCU234MB316GR
#10	23⁄4	Gray 01	T20	DCU234C316GR01	DCU234P316GR01	DCU234MB316GR01
#10	23⁄4	Gray 04	T20	DCU234C316GR04	DCU234P316GR04	DCU234MB316GR04
#10	23⁄4	Red	T20	DCU234C316RD	DCU234P316RD	DCU234MB316RD
#10	23⁄4	Red 01	T20	DCU234C316RD01	DCU234P316RD01	DCU234MB316RD01
#10	23⁄4	Tan	T20	DCU234C316TN	DCU234P316TN	DCU234MB316TN
#10	23⁄4	Tan 01	T20	DCU234C316TN01	DCU234P316TN01	DCU234MB316TN01
#10	23⁄4	Tan 02	T20	DCU234C316TN02	DCU234P316TN02	DCU234MB316TN02
#10	23⁄4	Tan 03	T20	DCU234C316TN03	DCU234P316TN03	DCU234MB316TN03

1.350 screws install approx. 100 sq. ft. of decking with framing at 16" on-center spacing. 2.1,750 screws install approx. 500 sq. ft. of decking with framing at 16" on-center spacing.

Type 316 Stainless Steel Painted Head (calleted)

Type	310 Sta	initess o	✓ 2¾" →		
Size	Length (in.)	Color	Bit Size	Carton (1,000 ct.)	PR0300S
#10	23⁄4	Brown 01	T20	DCU234S316BR01	✓
#10	23⁄4	Brown 05	T20	DCU234S316BR05	\checkmark
#10	23⁄4	Gray	T20	DCU234S316GR	\checkmark
#10	23⁄4	Gray 01	T20	DCU234S316GR01	\checkmark
#10	23⁄4	Gray 04	T20	DCU234S316GR04	\checkmark
#10	23⁄4	Red	T20	DCU234S316RD	\checkmark
#10	23⁄4	Red 01	T20	DCU234S316RD01	\checkmark
#10	23⁄4	Tan	T20	DCU234S316TN	\checkmark
#10	23⁄4	Tan 01	T20	DCU234S316TN01	\checkmark
#10	23⁄4	Tan 02	T20	DCU234S316TN02	\checkmark
#10	23⁄4	Tan 03	T20	DCU234S316TN03	\checkmark

Save Time and Money with Higher Installation Speeds and Consistent Performance

The Quik Drive[®] PRO300S decking system is ideal for driving collated Deck-Drive[™] DCU Composite and DCU Composite SS. Stand-up driving helps you save on labor, with less user fatigue and better fastening consistency.

The PRO300S Decking System Includes:

- PRO300S decking attachment (also sold separately)
- Extension for stand-up driving
- Decking nose clip for consistent screw placement
- Quiver for keeping screws at your fingertips
- Rugged tool case
- Choice of Makita® or DeWalt® screwdriver motors*
- Lifetime warranty (see strongtie.com/warranty for more information)



This flier is effective until June 30, 2023, and reflects information available as of June 1, 2021. This information is updated periodically and should not be relied upon after June 30, 2023. Contact Simpson Strong-Tie for current information and limited warranty or see strongtic.com.



System Options	Model No.
DeWalt 2,500 rpm screwdriver motor	PR0300SD25K
Makita 2,500 rpm screwdriver motor	PR0300SM25K
Bit pack - 10 each, T20 6-lobe	BITTX20-RC10
Bit pack – 3 each, T20 6-lobe	BITTX20-RC3

F-F-DCU21 6/21 exp. 6/23

2", 23/4"-



SIMPSON Strong-Tie