

5"

## Retain this label in place • Do not paint over label

### CARE AND MAINTENANCE

**Painting and Door Finish:** Bilco Basement Doors are supplied with a uniform baked-on Sherwin-Williams primer finish. If the door becomes scratched during the construction process or worn by long exposure, clean damaged areas as required with steel wool, sandpaper, or wire brush, and apply alkyd primer containing zinc oxide, iron oxide or similar rust inhibiting pigments before applying finish coat.

**IMPORTANT:** Door must be painted within **forty-five (45) days of installation**. Bilco recommends using Sherwin-Williams **All Surface Enamel A11 Series** in a white or light color. For best results, carefully follow the directions on the Sherwin-Williams label and apply one thin coat of paint followed by a second coat on both the exterior and interior primed steel surfaces of the door. Two quarts should be sufficient to coat the entire door.

**General Maintenance:** At least once a year remove any accumulation of dirt or leaves from the channel header at the top of the door frame. This channel should be kept clear so water will flow off freely in heavy rainstorms.

After a few years recaulking around the Bilco door may be necessary. Using exterior grade silicone or polyurethane caulk (opaque), caulk all around the exterior of the door frame where it meets the masonry.

## CAUTION

When the doors are open for access, the area should be personally guarded to prevent anyone from falling down the stairs. Doors should be closed and locked when not in use. **KEEP OFF DOORS TO AVOID INJURY** Surface may be slippery. In extreme conditions steel in the summer sun can become hot and cause injury.

## KEEP OFF DOORS

### Keyed Basement Door Lock Kit Available from Bilco

Easy to install, lock kit provides the convenience of keyed exterior access. Purchase on-line at [www.bilco.com](http://www.bilco.com)

For Customer Service,  
Please call 1-800-854-9724  
or log-on to [www.bilco.com](http://www.bilco.com)

Patent # 6,799,395

1ABC256 Rev 5.0

*Place Serial Number Label Here*

### RELEASED TO MANUFACTURING

DATE: 03/22/2011

APPROVED BY: D.J.C.

UNLESS OTHERWISE SPECIFIED:		NAME/#	DATE	<div style="display: flex; justify-content: space-between; font-size: 8px;"> <span>Manufacturers of Doors for Special Services</span> <span><b>THE BILCO COMPANY</b></span> </div> <div style="display: flex; justify-content: space-between; font-size: 8px;"> <span>New Haven, Connecticut 06505</span> </div>	
<small>UNLESS OTHERWISE SPECIFIED REMOVE ALL BURRS &amp; SHARP CORNERS DIMENSION TOLERANCES X.XXX +/- .010 X.XX +/- .015 X.X +/- .030 ANGLES +/- 2° FRACTIONS +/- 1/32</small>		DRAWN	ATR		09/25/06
INTERPRET GEOMETRIC TOLERANCING PER:		ORG. AUTHOR			ATR
MATERIAL		ORG. ECR			20921 09/25/06
FINISH		Q.A.			

DO NOT SCALE DRAWING

3RD-ANGLE PROJECTION

TITLE:		LABEL-PAINT, 5" X 7 3/4" (CARE & MAINTENANCE)	
SIZE	DWG. NO.	REV	
<b>A</b>	<b>ABC256</b>	<b>E</b>	
SCALE: 1:1		WEIGHT:	SHEET 1 OF 1

E	CHANGED "IMPORTANT" SECTION & UPDATED TO 5.0	29038	ATR	03/21/11
D	UPDATED LABEL TO REV. 4.0 PER S.W. CHANGES	27189	ATR	12/29/09
C	FIXED TYPO PROVIDES WAS PROVIES	25411	ATR	10/28/08
B	UPDATED LABEL TO REV. 3.0 PER S.W. CHANGES	24423	ATR	04/08/08
REV.	DESCRIPTION	ECR	BY	DATE

THIS DRAWING IS THE PROPERTY OF THE BILCO COMPANY AND INCORPORATES PROPRIETARY INFORMATION. PUBLICATION AND/OR PUBLIC DISTRIBUTION IN WHOLE OR IN PART IS EXPRESSLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF THE BILCO COMPANY. THE INFORMATION CONTAINED HEREIN REMAINS THE PROPERTY OF THE BILCO COMPANY. ALL RIGHTS RESERVED.