Item Number: A03562


- **WARNING** (To reduce the risk of fire, electric shock, or injury to persons):
- 1. We suggest installation by a **licensed electrician**.
- 2. Please read the instruction carefully and save it as you may need it at later time.
- 3. Before you start, **NEVER** attempt any work without shutting off the electricity until the work is done. A). Go to the main fuse, or circuit breaker, box in your home. Place the main power switch in the "**OFF**" position. B). Place the wall switch in the "**OFF**" position.
- 4. Mounting surface should be clean, dry, flat, strong enough and 1/4" larger than the canopy on all side. Any gaps between the mounting surface and canopy exceeding 3/16" should be corrected as required.
- 5. Make sure that the ceiling or wall can stand the weight of the lamp before fixture.
- 6. Make sure the voltage you are using is **120V**. The maximum wattage is **40W** per bulb.
- 7. Keep the lamp away from acidic and basic objects in case of damaging the surface of the lamp.
- 8. When replacing bulb, you should turn off or unplug the lamp and you must wait until it is cool as bulbs get hot quickly.
- 9. The safety instructions appearing in this manual are not meant to cover all possible conditions that may occur. It must be understood that common sense, caution and care must be used with any electrical products.


IMAGE FOR FINISHED PRODUCT:

FRONT VIEW SIDE VIEW

TOOLS REQUIRED (NOT INCLUDED):

Before doing assembly and installation please prepare the needed tools as below picture







ASSEMBLY & INSTALLATION INSTRUCTIONS:

- 1. Carefully remove the fixture from the carton and check that all parts and accessories are included as shown in the above illustration
- 2. Turn off power

Before you start to make installation, NEVER attempt any work without shutting off the electricity until the work is done. A). Go to the main fuse, or circuit breaker, box in your home. Place the main power switch in the "OFF" position. B). Place the wall switch in the "OFF" position. B). Place the wall switch in the "OFF" position.

3. Unscrew the threaded balls (F) from the back plate (E) then carefully remove the mounting plate assembly (B).





4. Attach the mounting plate assembly(B) to outlet box with mounting screws (D).


Carefully and gently pass the outlet box wires through the mounting plate assembly(B).

6. Make wire connections

Connect wires as below wires connecting shown. TAKE NOTE OF YOUR WIRE COLOR OF FIXTURE , NEVER CONNECT

WIRE TO GROUND WIRE


Connect ground wire according to below chart



Connect wires according to below chart

Connect Black or	Connect
Red Supply Wire to:	White Supply Wire to:
Black	White
*Parallel cord (round & smooth)	*Parallel cord (square & ridged)
Clear, Brown, Gold or Black	Clear, Brown, Gold or Black
without tracer	with tracer
Insulated wire (other than green)	Insulated wire (other than green
with copper conductor	with silver conductor
Note: When parallel wires (SPT I & 3 re used. The neutral wire is square s r ridged and the other wire will be ro hape or smooth (see illus.)	haped

Twist plastic wire connector (A)until wires are tightly joined together, wrap each connector with approved electrical tape and



8. Install bulbs (Not included. Please do not exceed the maximum capacity recommended on the socket.) Thread the jar (H)onto the lid (G) till tight.

Check everything is already installed properly, then you could turn on the light. Enjoy! 9.

CLEANING

To clean, wipe fixture with a soft cloth. Clean glass with a mild soap. Do not use abrasive materials such as scouring pads or powders, steel wool or abrasive paper.

ORDERING PARTS

Keep this sheet for future reference, and in case you need to order replacement parts. All parts for this fixture can be ordered from place of purchase. Be sure to use exact wording from illustration when ordering parts.

F

G

-H