

# DCF510 20V MAX\* XR® BRUSHLESS 3/8" & 1/2" SEALED HEAD RATCHET

Engineered with the professional in mind, the 20V MAX\* XR® Brushless 3/8" & 1/2" Sealed Head Ratchet has the power, versatility, and durability needed on the job. This cordless ratchet delievers 75 ft-lbs. of max torque and a no-load speed of 0-300 RPMs to fasten and remove stubborn nuts and bolts. The sealed head design and glass-filled nylon tool housing is designed to help prevent damage from automotive oils and solvents found on the job. Maximize versatility with the ability to quickly swap between interchangable 3/8" and 1/2" square drive anvils for a variety of applications, as well as quickly change from forward to reverse for more efficient working. Brighten your workspace with the integrated LED light to get to those hard to reach fasteners.



# 20V MAX\* XR® BRUSHLESS 3/8" & 1/2" SEALED HEAD RATCHET







<sup>\*</sup> Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

<b>SPECIFICATIONS</b>	
ANVIL TYPE	3/8 in. & 1/2 in. Square Drives
RPM (NO-LOAD)	0 – 300
MAX TORQUE	75 ft-lbs.
TOOL WEIGHT (TOOL ONLY)	2.65 lbs.
TOOL LENGTH	15 in.

## **TOOL WARRANTY**







LIMITED WARRANTY

SERVICE

MONEY BACK GUARANTEE

### **KIT OPTIONS**

#### DCF510B

(1) DCF510 Ratchet

State of the

(1) 3/8 in. Square Drive

(1) 1/2 in. Square Drive

(1) Kit Bag



#### DCF510GE1

(1) DCF510 Ratchet

(1) DCBP034G DEWALT POWERSTACK™
Oil-Resistant Compact Battery

(1) Charger

(1) 3/8 in. Square Drive

(1) 1/2 in. Square Drive

(1) Kit Bag

Copyright © 2023 DEWALT. The following are trademarks for one or more DEWALT power tools, accessories, anchors and concrete adhesives: The yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool

**DCF510SS**