

## 52" Ceiling Fan

Ceiling mounted • Wet location listed **PROGRESS LED**

### Description:

This 52" Smyrna ceiling fan features an LED light source, offering both form and function with energy- and cost-savings benefits. The light kit contains a clear hammered glass shade and contains a 17W dimmable 3000K LED module. The five-blade fan features a dual mount system and has an all weather wet location rating (ABS) to accommodate a variety of settings inside and outside of the home. Smyrna is available in two finish options: Antique Bronze and Forged Black. Can be used to comply with California Title 20.

### Specifications:

- Forged Black (-80) (Painted)
- Steel construction
- Clear hammered Diffuser
- Toasted Oak blades and a Forged Black finish
- A wall switch is included
- The five-blade Smyrna fan features a dual mount system and has an all weather wet location rating (ABS blades) to accommodate a variety of settings inside and outside of the home
- Indoor ceiling fan ideal for use in great rooms, living rooms, bedrooms and bonus rooms
- Ideal for Traditional exteriors
- Reversible motor for year round comfort allows you to choose either a down draft (summer) or an up draft (winter)
- As a general rule of thumb, lighting experts suggest this fan is ideal in a room size that ranges from 226- to 400-square feet
- UL Wet location listed for wet locations
- A 3/4" x 4-1/2" downrod is included. Longer accessory downrods can be ordered separately
- Can be used to comply with California Title 20.
- High Speed Energy Information: Airflow- 4585 cfm, Energy consumption- 58 watts (excluding lights), Airflow efficiency- 79 cfm/watt
- Limited Lifetime Warranty.
- Ceiling panCanopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 80' of wire supplied
- Meets California Title 24 JA8-2016

### Performance:

Number of Modules	1
Input Power	18w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1386/77 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50,000 (L70/TM-21)
FCC	Title 20
Min. Start Temp	-10 °C
Max. Operating Temp	40 °C
Warranty	Limited Lifetime warranty
Labels	UL Wet location listed
	Meets California Title 24 JA8-2016

**P2576-8030K**

### Images:



### Dimensions:

Diameter: 52"  
Height: 19-1/2"

