



Submitted Model No.:

Specific Features:





▲ Designate proper finish suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.



see what Deita can do[.]

KITCHEN FAUCETS

- Kylo™ Collection
- Single Handle Pull-Down

FEATURES:

- Touch-Clean[®] Technology
- DIAMOND Seal[®] Technology
 MagnaTite[®] Docking System
- 3-Function Pull-Down w/ShieldSpray TM
- Touch₂O® Technology

STANDARD SPECIFICATIONS:

- Max flow rate 1.8 gpm @ 60 psi, 6.8 L/min @ 414 kPa
- 1,2 or 3 hole mount (escutcheon optional, included)
- Diamond coated ceramic cartridge
- 3/8" O.D. straight, staggered PEX supply lines
- Spout rotates 360°
- Dual integral check valves in sprayer assembly
- Three-function wand; Aerated stream, spray or
- LED indicator light signals on-off, water temperature and low batteries
- Uses 6 AA (included) or 6 C (optional) batteries
- Optional (EP73954) 120V AC adapter available (3 prong grounded outlet required

WARRANTY

- · Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.

COMPLIES WITH:

• ASME A112.18.1 / CSA B125.1 Indicates compliance to ICC/ANSI A117.1 - Valve control only

Delta Faucet Company 55 E. 111th Street, Indianapolis, IN 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2023 Delta Faucet Company