



Z5760

0.5 - 1.0 gpf Back Spud Washout Urinal

TAG _____



Z5760 Series

- 0.5 - 1.0 gpf (gallons per flush)
- Vitreous china
- Washout flushing action
- 3/4" back spud
- 2" I.P.S. outlet flange and rubber gasket with integral trap
- 14" extended rim for handicap compliance when installed at proper height
- Shipping Weight: 65 lbs.

Engineering Specification:

- ☐ **Z5760** with 3/4" back spud, vitreous china, 0.5 gpf[1.9 Lpf] - 1.0 gpf [3.8 Lpf] low consumption, wall hung urinal with concealed wall hanger brackets.

Z5760 Series

Recommended Trim:

- ☐ **Z6195AV-WS1**

Aqua Vantage® AV 1.0 gpf low consumption concealed urinal flush valve.

Optional Water-Savings Trim:

- ☐ **Z6195AV-EWS**

Aqua Vantage® AV .5 gpf extra water savings concealed flush valve.

This space is for Architectural/engineering Approval

See Zurn One Systems for suggested packages.

These dimensions and specifications are subject to change without notice.

Fixture dimensions meet ANSI/ASME standard A112.19.2-2003 and CAN/CSA B45 requirements.

Meets the American Disabilities Guidelines and ANSI A117.1 requirements when urinal is installed 432mm (17") from finished floor.



ZURN INDUSTRIES, LLC. ♦ COMMERCIAL BRASS OPERATION
5900 ELWIN BUCHANAN DRIVE ♦ SANFORD NC 27330
Phone: 1-800-997-3876 ♦ Fax: 919-775-3541
www.zurn.com
In Canada: ZURN INDUSTRIES LIMITED
3544 Nashua Drive ♦ Mississauga, Ontario L4V1L2
Phone: 905-405-8272 Fax: 905-405-1292

Rev. C
Dwg. No. 82073

Date: 4/13/11
Product No. Z5760



TAG _____

- Z5760 with back spud

