74"		
	<b>4384V</b> 42 <sup>1</sup> / <sub>2</sub> " x 38 <sup>3</sup> / <sub>8</sub> "x 23"	
	Installation: Drop-in cannot be under mounted	
$42\frac{1}{2}"$ $31\frac{1}{2}"$ $0$ $31\frac{1}{2$	GENERAL SPECIFICATIONS: Material Acrylic Plumbed Weight : 165lbs / 75kg Soaker Weight :100 lbs / 61kg Average Fill: 60 gal to above jet level ELECTRICAL SPECIFICATIONS:	
83 <u>3</u> "	Required ElectricalService 110 VoltAir Bath or Whirlpool1-15 amp GFCIWhirlpool with Inline Heater1-20 amp GFCIWhirlpool and Air1-20 amp GFCISoaker1-20 amp GFCI	



## PACKAGES AND OPTIONS

Hydrotherapy Package	Package Contents	Part #
Soaker	Soaking bath - no jets, textured bottom	4384VS
Whirlpool	Adjustable pointed-massage jets, 1-hp pump, textured bottom	4384VH
Air Bath	Air jets, Air blower, Textured bottom	4384VA
Whirlpool and Air	Adjustable pointed-massage jets, 1-hp pump, Air jets Air blower, textured bottom	4384VD

- OPTIONS
- Colors Available White Biscuit
- Quick Ship reduces lead time call for availability
- Inline Heater with Pump Whirlpool or Whirlpool and Air
- Lift & Turn Drain Kit -Chrome, Brushed Nickel, White
- Color Match Jets.

## IMPORTANT INFORMATION

- Before ordering or installing, please consider future access to equipment.
- Add bedding compound to fully level and support bottom of tub. notice.
- Tubs equipped with an air bath or a pre-leveled
- foam base are designed to rest on the floor without bedding compound, provided the floor is level.
- Please measure tub on-site before building tub decking.
- $\bullet$  Jet, pump & blower locations are predetermined and cannot be changed.
- Suction and control locations may vary.
- Specifications and configurations are subject to change without notice.
- Measurements are +1/2" and are subject to change without notice.
- Measurements herein supersede all others published prior to publication date shown below.