



# CLEAR-SEAL

## PREMIUM LOW GLOSS SEALER

PRODUCT  
DATA SHEET

**DESCRIPTION:** Ready-to-use premium low gloss sealer that penetrates deeply to seal and protect painted, stained or bare concrete. It goes on milky white and dries to a low gloss finish, enhancing the natural character of your surface. CLEAR-SEAL is a durable urethane-fortified acrylic sealer with low odor, and low VOCs, so it's easy to work with and safe for the environment. It has excellent chemical resistance and repels stains.

**Typical Uses:**

- ✓ Pool Decks
- ✓ Driveways & Garages
- ✓ Patios & porches
- ✓ Sidewalks

**Important:** Read all directions thoroughly. Recommended: Wear gloves and safety glasses.

**SURFACE PREP\*:** *Note:* The surface should be clean and dry. You may need an oil stain remover such as SEAL-KRETE® Oil Stain Remover to lift stubborn oil stains. Pressure-washing is recommended.

**Bare Concrete:** Concrete must have cured for a minimum of 30 days. Etch smooth-finished concrete, such as basement or garage floors with a concrete etching solution like SEAL-KRETE Clean-N-Etch. *Note:* If etching with muriatic acid the area must be neutralized before proceeding. For more information visit [www.seal-krete.com](http://www.seal-krete.com).

**Painted Surfaces:** For use over one-part water-based coatings only; not recommended over acid-based stains or oil-based coatings. Freshly painted or stained surfaces must have cured for a minimum of 72 hours. Painted surfaces must be sound (not blistering or peeling). Existing painted surfaces should be cleaned with a solution of Trisodium Phosphate (TSP) and water. Rinse well and allow to dry.

**APPLICATION:** Read "LIMITATIONS" section before use. This product is ready to use; do not dilute. Stir gently; do not shake. Apply in light, even coats. One coat is recommended; however, over porous surfaces, like salttillo tile, or when a higher sheen is desired, apply a second coat. *Note:* Sealer goes on milky white but dries clear.

**Roller:** Dampen roller, remove excess water, then saturate roller with product. Keep a wet edge while rolling. Do not allow to puddle, foam or run. (Use a 1/4" nap for smooth surfaces, 3/8" nap for rough or porous surfaces.)

**Pump Sprayer:** Set at a fine spray and apply using a circular motion. To eliminate puddling or to achieve a more uniform finish, backroll immediately after spraying.

**COVERAGE:** 150-500 sq.ft. per gallon, depending on surface porosity.

**DRY TIME:** Dry to touch in 1 hour at 77°F (25°C) 50% RH. Recoat in 2 hours. Dry to foot traffic in 24 hours. Will accept vehicular traffic in 72 hours. Dry times should be extended in colder climates.

**CLEAN-UP & STORAGE:** Clean tools with soap and water immediately after use. Store in a dry area. KEEP FROM FREEZING.

**MAINTENANCE:** Clean with a mild soap and water solution. Do not use solvent-based cleaners.

**LIMITATIONS:** Temperatures should be 50° to 90°F (10° to 30°C) and should not fall below 50°F (10°C) within 24 hours of application. Do not apply if rain is expected within 12 hours. Do not use over acid-based stains, 2-part epoxies or oil-based paints. Do not use on glazed tile. Do not use in areas subject to hydrostatic pressure. Smooth-finished concrete may be slippery when wet; consider using an anti-skid additive like SEAL-KRETE Clear Grip on high foot traffic areas.

*\*Sanding or removing paint containing lead may be hazardous. For information contact the National Lead Information Center at 1-800-424-LEAD or [www.epa.gov/lead](http://www.epa.gov/lead).*

**CAUTION: CONTAINS PROPYLENE GLYCOL PHENYL ETHER. MAY CAUSE EYE AND SKIN IRRITATION. USE ONLY WITH ADEQUATE VENTILATION.**  
**FIRST AID:** In case of eye contact, flush with water for 15 minutes. If irritation persists, get medical attention. In case of skin contact, wash thoroughly with soap and water. If swallowed, drink 1-2 glasses of water and immediately contact medical services regarding any instructions to induce vomiting.  
**KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**



Product	No.	Unit	UPC Code	Carton Bar Code	Carton Size (W x D x H)	Carton Size (cubic ft / lbs)	Carton Qty	Pallet Qty
Clear-Seal Premium Low Gloss Sealer	365001	1 gallon	0 15944 36501 6	1 00 15944 36501 3	14.38 x 14.38 x 8.5	1.02 / 37.79	4	45 cs



# CLEAR-SEAL

## PREMIUM LOW GLOSS SEALER

- EXCELLENT DURABILITY
- INTERIOR/EXTERIOR USE
- FOR COATED & UNCOATED HORIZONTAL SURFACES

### TECHNICAL INFORMATION

- ASTM D-1475: pounds/gallon 8.45 ± .15
- Viscosity: 25 seconds, #4 cup
- ASTM E-70: pH 8.75
- ASTM D-2369-93: solids 11.50 ± 1%
- Clean-up: soap and water
- Shelf life: 2 years min. (closed container)
- Visual appearance: milky white (wet); dries clear
- ASTM D-1640: dry-to-touch 1 hour; dry to recoat 2 hours; dry to light foot traffic 24 hours; dry to vehicular traffic 72 hours
- ASTM D-3363 hardness: pencil F
- ASTM D-3359B intercoat adhesion: excellent
- Gloss: 25 (1 coat)
- ASTM G-53 ultraviolet resistance: excellent
- Gloss retention: excellent
- Tire marking: resistant to most tires
- Proprietary urethane-acrylic blend
- VOC < 50 g/L – Waterproofing Sealer Category  
Low Solids Coating – Reporting VOC of Material

### CHEMICAL/SOLVENT RESISTANCE - ASTM D-1308

(One hour spot test)

- Gasoline: resistant
- Oil: resistant
- Water: resistant
- Salt: resistant
- Chlorine: resistant

### FEATURES

- Seals and protects painted, stained or bare concrete
- Seals in color
- Reduces pockmarking and cracking
- Clear finish, will not yellow
- Premium, urethane-fortified acrylic formula

### LIQUID PROPERTIES

- Water-Based
- Odor: Low

**LIMITED WARRANTY:** Manufacturer/Seller makes no warranty of any kind except that this product is free from defect and is of merchantable quality. Buyer remedy for breach of warranty is limited to replacement of SEAL-KRETE product or refund of purchase price. Convenience Products will not be responsible for labor or the cost of labor for removal or application of any product.

**TECHNICAL SUPPORT:** For more information on surface prep or application guidelines, or to obtain a Material Safety Data Sheet, call 1-800-323-7357, M-F (8:00 am–5:00 pm EST) or visit our website at [www.seal-krete.com](http://www.seal-krete.com).

**WATERPROOFS & SEALS PAINTED, STAINED, TEXTURED & BARE CONCRETE SURFACES**

**RESISTANT TO MOISTURE, SALT, CHLORINE, OIL & HOT TIRE PICKUP**

**HIGHLY DURABLE NON-YELLOWING ACRYLIC**

WATERPROOFS CONCRETE SURFACES



RESISTS HOT TIRE PICKUP



PROVIDES A DURABLE, NON-YELLOWING FINISH



11 Hawthorn Pkwy, Vernon Hills, IL 60061

Questions or comments? Call 1-800-323-7357

[www.seal-krete.com](http://www.seal-krete.com)

©2017 Rust-Oleum Corp

PREMIUM PROTECTIVE SEALER

64068-012717-SK